


JKL LAMP PART NUMBER	COLOR	STARTING CIRCUIT VOLTAGE VS (Vrms)	OPERATING LAMP VOLTAGE VL (Vrms)	OPERATING LAMP CURRENT IL (mA rms)	BRIGHTNESS (CANDELA/m ²)	*RATED LIFE (HRS)
BF26188-20B	LCD HIGH OUTPUT WHITE 5600°k RGB	1000 @ 0°C	420	5	30,000 ± 10%	20,000

* RATED LIFE IS DEFINED AS THE POINT AT WHICH THE INTENSITY BECOMES 50% OF THE INITIAL RATING.

			METRIC  THIRD ANGLE PROJECTION		DIMENSIONS ARE IN MILLIMETERS TOLERANCE UNLESS OTHERWISE SPECIFIED 1 PL +/- 0 2 PL +/- 0 ANGLE +/- 0		JKL COMPONENTS CORPORATION					
					TITLE MINIATURE COLD CATHODE FLUORESCENT LAMP							
B DIM CORRECT. AND 188+/-5.0 TO 188+/-3.0 A STARTING & OPERATING VOLTAGE CHANGE RELEASED			DRAWN BY L. WENGSTROM		APPVD BY DATE FD 10/17/00		SIZE A		FSCM NO. 55335		DRAWING NO. BF26188-20B	
REV. NO. DESCRIPTION/ECO NUMBER APPVD DATE			- CAD DRAWING - MANUAL REVISIONS NOT PERMITTED		SCALE NONE		RELEASED DATE 3/13/98		REVISION DATE 10/17/00		REV. NO. B SHEET 1 OF 1	