



DATE	REVISIONS	REV
9-22-94	REDRAWN./	A

DRAWING NUMBER	REV
LDS-A404RU	A



PIN NO. 6 (NC)  
NO PIN NOS. 4,5,12

ELECTRO-OPTICAL CHARACTERISTICS  $T_A = 25^\circ\text{C}$   $I_f = 10\text{mA}$

PARAMETER	MIN	TYP	MAX	UNITS	TEST COND
PEAK WAVELENGTH		635 (ORANGE)		nm	
FORWARD VOLTAGE		2.1	2.6	$V_f$	
REVERSE VOLTAGE	5.0			$V_r$	$I_f = 100\mu\text{A}$
AXIAL INTENSITY		1400		ucd	$I_f = 10\text{mA}$
EMITTED COLOR	ORANGE/RED				
EPOXY SEGMENT	ORANGE				
FONT COLOR	ORANGE				

LIMITS OF SAFE OPERATION PER CHIP AT  $25^\circ\text{C}$

PARAMETER	MAX	UNITS
PEAK FORWARD CURRENT*	50	mA
STEADY CURRENT	20	mA
POWER DISSIPATION	416	mW
DERATE FROM $25^\circ\text{C}$	N/A	mW/ $^\circ\text{C}$
OPERATING, STORAGE TEMP	-25 TO +80	$^\circ\text{C}$
LEAD SOLDERING TEMP	+230	$^\circ\text{C}$
2.0mm FROM BODY		3 SEC. MAX

\*  $t < 10\mu\text{s}$

NOTES:

- UNITS: mm (INCHES). TOLERANCE: 0.25 (0.01"), UNLESS OTHERWISE SPECIFIED.
- $I_v$  TESTED CONDITION  $I_f = 10\text{mA}$  AND THE LISTED  $I_v$  IS THE AVERAGE INTENSITY FOR EVERY SEGMENT LISTED.

**LUMEX**  
OPTO COMPONENTS INC.

290 E. HELLEN ROAD  
PALATINE, ILLINOIS 60067  
(847) 359-2790

CONFIDENTIAL INFORMATION  
THE INFORMATION CONTAINED IN THIS DOCUMENT IS THE PROPERTY OF LUMEX OPTO/COMPONENTS, INC. EXCEPT AS SPECIFICALLY AUTHORIZED IN WRITING BY LUMEX OPTO/COMPONENTS, INC., THE HOLDER OF THIS DOCUMENT SHALL KEEP ALL INFORMATION CONTAINED HEREIN CONFIDENTIAL AND SHALL PROTECT SAME IN WHOLE OR IN PART FROM DISCLOSURE AND DISSEMINATION TO ALL THIRD PARTIES.

DATE: 10-19-92	DWN:	CHK'D:	APPD:
SCALE: N/A			
.40" RED, SEVEN SEGMENT DISPLAY, COMMON ANODE			
PAGE 1 OF 1	DRAWING NUMBER LDS-A404RU	REV A	