

DEVICELINX® EMBEDDED NETWORKING MODULES

lantronix.com



Features

	XPort [®]	XPort [®] Pro	XPort [®] Direct+	MatchPort [®] b/g	MatchPort [®] b/g Pro	MatchPort [®] AR	MatchPort [®] NR	PremierWave EN
Operating system	CoBos	Evolution OS [™] /Linux	CoBos	CoBos	Evolution OS [™]	Evolution OS [™] /Linux	CoBos	Linux
10/100 Ethernet (*external RJ45 jack)	•	•	•	•*	•*	•*	•*	•*
Wireless 802.11 b/g (*a/b/g/n)				•	•			•*
LAN → 802.11 bridging				•	•			•
TCP / UDP client-server	•	•	•	•	•	•	•	•
Telnet	•	•	•	•	•	•	•	•
DHCP, BOOTP & AUTOIP	•	•	•	•	•	•	•	•
TFTP (*FTP)	•	•*	•	•	•*	•*	•	•*
PPP		•			•	•		•
SNMP	•	•	•	•	•	•	•	•
Web server - HTTP	•	•	•	•	•	•	•	•
Web server - CGI (*Custom)	•*	•	•*	•*	•	•	•*	•*
Web server - AJAX		•			•	•		•
SSL Secure web server		•			•	•		•
SSL Secure data tunneling		•			•	•		•
SSH client & server		•			•	•		•
Enterprise-grade security & authentication protocols for WLAN					•			•
VIP Access (*Evolution)		•*			•	•		•
IPv6 (*Linux SDK Development Platform)		•*				•*		•*
Java support	•	•	•	•	•	•	•	•
AES Encryption (*Option)	•*	•	•	•	•	•	•	•
Max Configurable GPIO pins (*RTS/CTS on configurable pins)	3*	3*	3	8	7	7	8	9
Software Development Kit (*CPK)	•*	•	•*	•*	•	•	•*	•
Flash/RAM	512KB/256KB	16MB/8MB	512KB/256KB	2MB/256KB	8MB/8MB	4MB/8MB	2MB/256KB	64MB/64MB
Maximum serial data rate	921 Kbps	921 Kbps	921 Kbps	921 Kbps	230 Kbps	230 Kbps	921 Kbps	921 Kbps
Web manager (for configuration)	•	•	•	•	•	•	•	•
Email client (*Subject Line Only)	•*	•	•*	•*	•	•	•*	•
Operating Temperature (C°/F°)	-40 to 85°C or 0 to 70°C -40 to 185°F or 32 to 158°F	-40 to 85°C -40 to 185°F	-40 to 85°C -40 to 185°F	-40 to 70°C -40 to 158°F	-40 to 70°C -40 to 158°F	-40 to 70°C -40 to 158°F	-40 to 85°C -40 to 185°F	-40 to 85°C -40 to 185°F
Dimensions (mm)	33.9 x 16.25 x 13.5	33.9 x 16.25 x 13.5	44.3 x 31.75 x 11.76	44.4 x 44.4 x 10.4	44.4 x 44.4 x 10.4	44.4 x 44.4 x 10.4	44.4 x 44.4 x 10.4	30 x 55 x 8
Serial Interface/# of Ports (*5V Tolerance)	CMOS 3.3V*/1	CMOS 3.3V*/1	CMOS 3.3V*/1	CMOS 3.3V*/2	CMOS 3.3V/2	CMOS 3.3V/2	CMOS 3.3V*/2	CMOS 3.3V/2
SmartRoom[™]				•	•			•

Lantronix Corporate Headquarters
167 Technology Drive
Irvine CA 92618
t: 800.422.7055
sales@lantronix.com

European Headquarters
t: +31 (0) 76 52 36 74 4
EMEA@lantronix.com

Asia/Pacific Headquarters
t: +852 3428 2338
asiapacific_sales@lantronix.com

Japan Headquarters
t: +81.3.6277.8802
japan_sales@lantronix.com

© 2011, Lantronix, Inc. Lantronix is a registered trademark and DeviceLinx and Evolution OS are trademarks of Lantronix, Inc. All other trademarks are the property of their respective owners. Specifications subject to change without notice. All rights reserved. 940-005-R Rev A 03/11

