

# Blackhawk™ USB560BP JTAG Emulator for TI DSPs

TI DSP platforms: TMS320C6000™, TMS320C5000™,  
TMS320C2000™, OMAP™, DaVinci™

Compatible Operating Systems: Windows® 2000, XP and Vista

The compact bus-powered Blackhawk USB560BP is the third generation of the widely used XDS560-class emulator first introduced by Blackhawk and the only bus-powered USB JTAG Emulator that supports all of the advanced capabilities of Texas Instruments latest DSPs. These capabilities include high-speed Real-Time Data Exchange HS-RTDX™, lightning speed downloads and Advanced Event Triggering to quickly find and fix real-time software problems.

**The compact emulator is under 5 ounces  
and needs no external power!**

Features include a variable TCK (timing clock) up to 50 MHz and highly flexible 8 inch cable assembly suitable for use from 5.0 volts down to 0.5 volts to support TI low-voltage device roadmap. Software compatibility with all versions of Code Composer Studio™ (CCStudio) integrated development environment (IDE) v2.2 and later. Drivers are provided for Windows® 2000, XP and Vista. Additionally, 64-bit drivers are available for XP Pro x64 and Vista x64. All driver updates are available for download free-of-charge from our website.

The Blackhawk USB560BP JTAG Emulator supports TMS320, TMS470 (ARM®) and OMAP™ families including the DaVinci™ platform. The USB560BP JTAG Emulator is also compatible with the Code Composer Studio Flash-burner utility.

Blackhawk JTAG Emulators are available from a world wide network of industry resellers.

## ABOUT BLACKHAWK

Blackhawk™ is the first to introduce a USB JTAG Emulator for Texas Instruments DSPs and is a member of the TI DSP Third Party Network. Blackhawk™ is a business unit of EWA/EWA Technologies, Inc. with headquarters in Herndon, Virginia. Founded in 1977, EWA, Inc., is a broad-based technology company with 1,000 employees located in corporate offices and on-site throughout the U.S., Canada, and Australia providing professional services and specialized products to both U.S. and foreign customers. Committed to quality and customer support, EWA prides itself on overcoming technological challenges, delivering on-time for its customers, and providing continuing service.



3rd Generation  
Technology

## Features

- **USB Bus-powered, needs no power supply**
- High-speed RTDX™ Support with data rates of over 2 MB/sec
- New compact pod with status indicator LED
- High-speed USB 2.0 (480 Mbits/sec) port
- Auto-sensing low I/O voltage support
- Real-time, non-intrusive Advanced Event Triggering capability
- Native ADAPTIVE CLOCKING support for TI ARM-based devices
- Windows® Plug n' Play Installation
- Up to 100 times faster than XDS510 emulators
- Full Code Composer Studio IDE compatibility for v2.2 and later
- **Remote Ethernet Software Available (\$495)**

## System Requirements

- PC running Windows® 2000, XP or Vista
- Code Composer Studio IDE v2.2 or later
- Free USB 1.1 or 2.0 port (2.0 preferred)
- CD-ROM drive for driver installation
- Target hardware with 20-pin cTI JTAG header

## Application Areas

Audio, Automotive, Broadband Solutions, Digital Controls, Imaging & Video, Military, Optical Networking, Telephony, Wireless Communications.

**Part Number BH-USB-560BP**

# Blackhawk Emulators

123 Gaither Drive • Mt. Laurel, NJ 08054 • 877-983-4514 • [www.blackhawk-dsp.com](http://www.blackhawk-dsp.com)



© 2008 EWA Technologies, Inc. 6/2008

Blackhawk is a registered trademark of EWA Technologies, Inc. Other product names used herein are trademarks of their respective companies.