

AISG Integrated Transceiver**General Description**

The MAX9947 is an AISG-compliant, fully integrated transceiver.

The MAX9947 receiver offers a typical dynamic range of 20dB and integrates a bandpass filter that operates in the 2.176MHz frequency with a narrow 200kHz bandwidth.

The MAX9947 transmitter integrates a bandpass filter that is compliant with the AISG spectrum emission profile. It can modulate OOK signals up to 115.2kbps. The output power can be varied with external resistors from +7dBm to +12dBm to compensate for loss in the external circuitry and cabling.

The MAX9947 also features a direction output to facilitate the RS-485 bus arbitration in tower-mounted equipment.

The MAX9947 is available in a small, 3mm x 3mm 16-pin TQFN and is rated for operation in the -40°C to +85°C temperature range.

Applications

Base Stations
Tower Equipment

Features

- ◆ **Receiver Wide Input Dynamic Range**
-15dBm to +5dBm in 50Ω
- ◆ **Variable Transmitter Output Level** from +7dBm to +12dBm
- ◆ **AISG-Compliant Output Emission Profile**
- ◆ **AutoDirection Output**
- ◆ **No Need of Microcontrollers to Handle Bus Arbitration in Tower-Mounted Equipment**
- ◆ **Supports All AISG Data Rates**
9.6kbps
38.4kbps
115.2kbps
- ◆ **Bandpass Filter Compliant with AISG Protocol**
Centered Around 2.176MHz
- ◆ **3.0V to 5.5V Voltage Supply**
- ◆ **Independent Logic Supply**
- ◆ **Small, 3mm x 3mm 16-Pin TQFN Package**

Ordering Information

PART	TEMP RANGE	PIN-PACKAGE	TOP MARK
MAX9947ETE+	-40°C to +85°C	16 TQFN-EP*	AFH

+Denotes a lead(Pb)-free/RoHS-compliant package.

*EP = Exposed pad. Connect EP to GND to enhance thermal dissipation.

Functional Diagram