

## Surface Mount Trench MOS Barrier Schottky Rectifier



### FEATURES

- Low profile package
- Ideal for automated placement
- Trench MOS Schottky technology
- Low power losses, high efficiency
- Low forward voltage drop
- Meets MSL level 1, per J-STD-020, LF maximum peak of 260 °C
- Compliant to RoHS directive 2002/95/EC and in accordance to WEEE 2002/96/EC



**RoHS**  
COMPLIANT

### TYPICAL APPLICATIONS

For use in low voltage, high frequency inverters, freewheeling, dc-to-dc converters, and polarity protection applications.

### MECHANICAL DATA

**Case:** DO-214AC (SMA)

Molding compound meets UL 94 V-0 flammability rating  
Base P/N-E3 - RoHS compliant, commercial grade

**Terminals:** Matte tin plated leads, solderable per J-STD-002 and JESD 22-B102

E3 suffix meets JESD 201 class 1A whisker test

**Polarity:** Color band denotes the cathode end

| PRIMARY CHARACTERISTICS |        |
|-------------------------|--------|
| $I_{F(AV)}$             | 2.0 A  |
| $V_{RRM}$               | 100 V  |
| $I_{FSM}$               | 60 A   |
| $E_{AS}$                | 24 mJ  |
| $V_F$ at $I_F = 2.0$ A  | 0.56 V |
| $T_J$ max.              | 150 °C |

| MAXIMUM RATINGS ( $T_A = 25$ °C unless otherwise noted)                               |                |               |      |
|---|----------------|---------------|------|
| PARAMETER   | SYMBOL         | VSSA210       | UNIT |
| Device marking code   |                | V2B           |      |
| Maximum repetitive peak reverse voltage   | $V_{RRM}$      | 100           | V    |
| Maximum DC forward current  | $I_F^{(1)}$    | 2.0           | A    |
|   | $I_F^{(2)}$    | 1.7           |      |
| Peak forward surge current 10 ms single half sine-wave superimposed on rated load     | $I_{FSM}$      | 60            | A    |
| Non-repetitive avalanche energy at $T_J = 25$ °C, $L = 60$ mH                         | $E_{AS}$       | 24            | mJ   |
| Peak repetitive reverse current at $t_p = 2$ $\mu$ s, 1 kHz, $T_J = 38$ °C $\pm$ 2 °C | $I_{RRM}$      | 1.0           | A    |
| Operating junction and storage temperature range                                      | $T_J, T_{STG}$ | - 40 to + 150 | °C   |

#### Notes

(1) Mounted on 8 mm x 8 mm pad areas, 1 oz. FR4 P.C.B.

(2) Free air, mounted on recommended copper pad area

| ELECTRICAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                         |                         |                               |               |      |      |
|--|-------------------------|-------------------------|-------------------------------|---------------|------|------|
| PARAMETER  | TEST CONDITIONS         |                         | SYMBOL                        | TYP.          | MAX. | UNIT |
| Breakdown voltage  | I <sub>R</sub> = 1.0 mA | T <sub>A</sub> = 25 °C  | V <sub>BR</sub>               | 100 (minimum) | -    | V    |
| Instantaneous forward voltage  | I <sub>F</sub> = 2.0 A  | T <sub>A</sub> = 25 °C  | V <sub>F</sub> <sup>(1)</sup> | 0.61          | 0.70 |      |
|  |                         | T <sub>A</sub> = 125 °C |                               | 0.56          | 0.65 |      |
| Reverse current  | V <sub>R</sub> = 70 V   | T <sub>A</sub> = 25 °C  | I <sub>R</sub> <sup>(2)</sup> | 1.0           | -    | μA   |
|  |                         | T <sub>A</sub> = 125 °C |                               | 0.95          | -    | mA   |
|  | V <sub>R</sub> = 100 V  | T <sub>A</sub> = 25 °C  |                               | 3.5           | 150  | μA   |
|  |                         | T <sub>A</sub> = 125 °C |                               | 2.2           | 15   | mA   |
| Typical junction capacitance   | 4.0 V, 1 MHz            |                         | C <sub>J</sub>                | 175           | -    | pF   |

Notes

- (1) Pulse test: 300 μs pulse width, 1 % duty cycle
- (2) Pulse test: Pulse width ≤ 40 ms

| THERMAL CHARACTERISTICS (T <sub>A</sub> = 25 °C unless otherwise noted) |                                 |         |      |
|---|---------------------------------|---------|------|
| PARAMETER   | SYMBOL                          | VSSA210 | UNIT |
| Typical thermal resistance  | R <sub>θJA</sub> <sup>(1)</sup> | 135     | °C/W |
|   | R <sub>θJM</sub> <sup>(2)</sup> | 25      |      |

Notes

- (1) Free air, mounted on recommended P.C.B. 1 oz. pad area. Thermal resistance R<sub>θJA</sub> - junction to ambient
- (2) Units mounted on P.C.B. with 8 mm x 8 mm copper pad areas. R<sub>θJM</sub> - junction to mount

| ORDERING INFORMATION (Example) |                 |                        |               |                                    |
|--------------------------------|-----------------|------------------------|---------------|------------------------------------|
| PREFERRED P/N                  | UNIT WEIGHT (g) | PREFERRED PACKAGE CODE | BASE QUANTITY | DELIVERY MODE                      |
| VSSA210-E3/61T                 | 0.064           | 61T                    | 1800          | 7" diameter plastic tape and reel  |
| VSSA210-E3/5AT                 | 0.064           | 5AT                    | 7500          | 13" diameter plastic tape and reel |

RATINGS AND CHARACTERISTICS CURVES

(T<sub>A</sub> = 25 °C unless otherwise noted)




Fig. 1 - Maximum Forward Current Derating Curve




Fig. 2 - Forward Power Loss Characteristics




Fig. 3 - Typical Instantaneous Forward Characteristics




Fig. 5 - Typical Junction Capacitance




Fig. 4 - Typical Reverse Characteristics






Fig. 6 - Typical Transient Thermal Impedance

**PACKAGE OUTLINE DIMENSIONS** in inches (millimeters)

**DO-214AC (SMA)**



**Mounting Pad Layout**





## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk and agree to fully indemnify and hold Vishay and its distributors harmless from and against any and all claims, liabilities, expenses and damages arising or resulting in connection with such use or sale, including attorneys fees, even if such claim alleges that Vishay or its distributor was negligent regarding the design or manufacture of the part. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.