

International
IOR Rectifier

11DQ03
 11DQ04

SCHOTTKY RECTIFIER

1.1 Amp


Major Ratings and Characteristics

Characteristics	Values	Units
$I_{F(AV)}$ Rectangular waveform	1.1	A
V_{RRM}	30/40	V
I_{FSM} @ $t_p = 5 \mu s$ sine	225	A
V_F @ 1 Apk, $T_J = 25^\circ C$	0.55	V
T_J range	-40 to 150	$^\circ C$

Description/ Features

The 11DQ.. axial leaded Schottky rectifier has been optimized for very low forward voltage drop, with moderate leakage. Typical applications are in switching power supplies, converters, free-wheeling diodes, and reverse battery protection.

- Low profile, axial leaded outline
- High purity, high temperature epoxy encapsulation for enhanced mechanical strength and moisture resistance
- Very low forward voltage drop
- High frequency operation
- Guard ring for enhanced ruggedness and long term reliability
- Lead-Free plating



Voltage Ratings

Part number	11DQ03	11DQ04
V _R Max. DC Reverse Voltage (V)	30	40
V _{RWM} Max. Working Peak Reverse Voltage (V)		

Absolute Maximum Ratings

Parameters	11DQ..	Units	Conditions
I _{F(AV)} Max. Average Forward Current * See Fig. 4	1.1	A	50% duty cycle @ T _C = 75 °C, rectangular wave form
I _{FSM} Max. Peak One Cycle Non-Repetitive Surge Current * See Fig. 6	225	A	Following any rated load condition and with rated V _{RRM} applied
	35		
E _{AS} Non-Repetitive Avalanche Energy	3.0	mJ	T _J = 25 °C, I _{AS} = 1.0 Amps, L = 6 mH
I _{AR} Repetitive Avalanche Current	1.0	A	Current decaying linearly to zero in 1 µsec Frequency limited by T _J max. V _A = 1.5 x V _R typical

Electrical Specifications

Parameters	11DQ..	Units	Conditions
V _{FM} Max. Forward Voltage Drop * See Fig. 1 (1)	0.55	V	@ 1A T _J = 25 °C
	0.71	V	@ 2A
	0.50	V	@ 1A T _J = 125 °C
	0.61	V	@ 2A
I _{RM} Max. Reverse Leakage Current * See Fig. 2 (1)	1.0	mA	T _J = 25 °C
	6.0	mA	T _J = 125 °C V _R = rated V _R
C _T Typical Junction Capacitance	60	pF	V _R = 5V _{DC} (test signal range 100Khz to 1Mhz) 25 °C
L _S Typical Series Inductance	8.0	nH	Measured lead to lead 5mm from package body
dv/dt Max. Voltage Rate of Change	10000	V/µs	(Rated V _R)

(1) Pulse Width < 300µs, Duty Cycle < 2%

Thermal-Mechanical Specifications

Parameters	11DQ..	Units	Conditions
T _J Max. Junction Temperature Range (*)	-40 to 150	°C	
T _{stg} Max. Storage Temperature Range	-40 to 150	°C	
R _{thJA} Max. Thermal Resistance Junction to Ambient	100	°C/W	DC operation Without cooling fin
R _{thJL} Typical Thermal Resistance Junction to Lead	81	°C/W	DC Operation (* See Fig. 4)
wt Approximate Weight	0.33(0.012)	g (oz.)	
Case Style	DO-204AL(DO-41)		

(*) $\frac{dP_{tot}}{dT_J} < \frac{1}{R_{th(j-a)}}$ thermal runaway condition for a diode on its own heatsink




Fig. 1 - Max. Forward Voltage Drop Characteristics




Fig. 2 - Typical Values Of Reverse Current Vs. Reverse Voltage




Fig. 3 - Typical Junction Capacitance Vs. Reverse Voltage




Fig. 4 - Max. Allowable Case Temperature Vs. Average Forward Current




Fig. 5 - Forward Power Loss Characteristics




Fig. 6 - Max. Non-Repetitive Surge Current

(2) Formula used: $T_C = T_J - (Pd + Pd_{REV}) \times R_{thJC}$;
 $Pd = \text{Forward Power Loss} = I_{F(AV)} \times V_{FM} @ (I_{F(AV)} / D)$ (see Fig. 6);
 $Pd_{REV} = \text{Inverse Power Loss} = V_{R1} \times I_{R1} (1 - D)$; $I_{R1} @ V_{R1} = 80\% \text{ rated } V_R$

Ordering Information Table

Device Code	
11	D
Q	04
TR	
①	②
③	④
⑤	

<table border="1"> <tr><td>1</td></tr> <tr><td>2</td></tr> <tr><td>3</td></tr> <tr><td>4</td></tr> <tr><td>5</td></tr> </table>	1	2	3	4	5	<ul style="list-style-type: none"> - 11 = 1.1A (Axial and small packages - Current is x10) - D = DO-41 package - Q = Schottky Q.. Series - 04 = Voltage Ratings - TR = Tape & Reel package (5000 pcs) - = Box package (1000 pcs)
1						
2						
3						
4						
5						

04 = 40V
 03 = 30V

Data and specifications subject to change without notice.
 This product has been designed and qualified for Industrial Level and Lead-Free.
 Qualification Standards can be found on IR's Web site.



Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.