


IRFIBE30GPbF

HEXFET® Power MOSFET

- Isolated Package
- High Voltage Isolation= 2.5KVRMS ⑤
- Sink to Lead Creepage Dist.= 4.8mm
- Dynamic dv/dt Rating
- Low Thermal Resistance
- Lead-Free




$V_{DSS} = 800V$
 $R_{DS(on)} = 3.0\Omega$
 $I_D = 2.1A$

Description

Third Generation HEXFETs from International Rectifier provide the designer with the best combination of fast switching, ruggedized device design, low on-resistance and cost-effectiveness.

The TO-220 Fullpak eliminates the need for additional insulating hardware in commercial-industrial applications. The moulding compound used provides a high isolation capability and a low thermal resistance between the tab and external heatsink. This isolation is equivalent to using a 100 micron mica barrier with standard TO-220 product. The Fullpak is mounted to a heatsink using a single clip or by a single screw fixing.



Absolute Maximum Ratings

| | Parameter | Max. | Units |
|---------------------------|---|-----------------------|-------|
| $I_D @ T_C = 25^\circ C$ | Continuous Drain Current, $V_{GS} @ 10 V$ | 2.1 | A |
| $I_D @ T_C = 100^\circ C$ | Continuous Drain Current, $V_{GS} @ 10 V$ | 1.4 | |
| I_{DM} | Pulsed Drain Current ① | 8.4 | |
| $P_D @ T_C = 25^\circ C$ | Power Dissipation | 35 | W |
| | Linear Derating Factor | 0.28 | W/°C |
| V_{GS} | Gate-to-Source Voltage | ± 20 | V |
| E_{AS} | Single Pulse Avalanche Energy ② | 240 | mJ |
| I_{AR} | Avalanche Current ① | 2.1 | A |
| E_{AR} | Repetitive Avalanche Energy ① | 3.5 | mJ |
| dv/dt | Peak Diode Recovery dv/dt ③ | 2.0 | V/ns |
| T_J T_{STG} | Operating Junction and Storage Temperature Range | -55 to +150 | °C |
| | Soldering Temperature, for 10 seconds | 300 (1.6mm from case) | |
| | Mounting Torque, 6-32 or M3 screw | 10 lbf•in (1.1 N•m) | |


Thermal Resistance

| | Parameter | Min. | Typ. | Max. | Units |
|-----------------|---------------------|------|------|------|-------|
| $R_{\theta JC}$ | Junction-to-Case | — | — | 3.6 | °C/W |
| $R_{\theta JA}$ | Junction-to-Ambient | — | — | 65 | |


IRFIBE30GPbF

International
IR Rectifier

Electrical Characteristics @ $T_J = 25^\circ\text{C}$ (unless otherwise specified)

| | Parameter | Min. | Typ. | Max. | Units | Test Conditions |
|---------------------------------|--------------------------------------|------|------|------|----------|--|
| $V_{(BR)DSS}$ | Drain-to-Source Breakdown Voltage | 800 | --- | --- | V | $V_{GS}=0V, I_D=250\mu A$ |
| $\Delta V_{(BR)DSS}/\Delta T_J$ | Breakdown Voltage Temp. Coefficient | --- | 0.90 | --- | V/°C | Reference to 25°C , $I_D=1\text{mA}$ |
| $R_{DS(on)}$ | Static Drain-to-Source On-Resistance | --- | --- | 3.0 | Ω | $V_{GS}=10V, I_D=1.3A$ ④ |
| $V_{GS(th)}$ | Gate Threshold Voltage | 2.0 | --- | 4.0 | V | $V_{DS}=V_{GS}, I_D=250\mu A$ |
| g_{fs} | Forward Transconductance | 1.7 | --- | --- | S | $V_{DS}=50V, I_D=1.3A$ ④ |
| I_{DSS} | Drain-to-Source Leakage Current | --- | --- | 100 | μA | $V_{DS}=800V, V_{GS}=0V$ |
| | | --- | --- | 500 | | $V_{DS}=640V, V_{GS}=0V, T_J=125^\circ\text{C}$ |
| I_{GSS} | Gate-to-Source Forward Leakage | --- | --- | 100 | nA | $V_{GS}=20V$ |
| | Gate-to-Source Reverse Leakage | --- | --- | -100 | | $V_{GS}=-20V$ |
| Q_g | Total Gate Charge | --- | --- | 78 | nC | $I_D=4.1A$ |
| Q_{gs} | Gate-to-Source Charge | --- | --- | 9.6 | | $V_{DS}=400V$ |
| Q_{gd} | Gate-to-Drain ("Miller") Charge | --- | --- | 45 | | $V_{GS}=10V$ See Fig. 6 and 13 ④ |
| $t_{d(on)}$ | Turn-On Delay Time | --- | 12 | --- | ns | $V_{DD}=400V$ |
| t_r | Rise Time | --- | 33 | --- | | $I_D=4.1A$ |
| $t_{d(off)}$ | Turn-Off Delay Time | --- | 82 | --- | | $R_G=12\Omega$ |
| t_f | Fall Time | --- | 30 | --- | | $R_D=95\Omega$ See Figure 10 ④ |
| L_D | Internal Drain Inductance | --- | 4.5 | --- | nH | Between lead, 6 mm (0.25in.) from package and center of die contact  |
| L_S | Internal Source Inductance | --- | 7.5 | --- | | |
| C_{iss} | Input Capacitance | --- | 1300 | --- | pF | $V_{GS}=0V$ |
| C_{oss} | Output Capacitance | --- | 310 | --- | | $V_{DS}=25V$ |
| C_{rss} | Reverse Transfer Capacitance | --- | 190 | --- | | $f=1.0\text{MHz}$ See Figure 5 |
| C | Drain to Sink Capacitance | --- | 12 | --- | | $f=1.0\text{MHz}$ |

Source-Drain Ratings and Characteristics

| | Parameter | Min. | Typ. | Max. | Units | Test Conditions |
|----------|--|---|------|------|---------|--|
| I_S | Continuous Source Current (Body Diode) | --- | --- | 2.1 | A | MOSFET symbol showing the integral reverse p-n junction diode.  |
| I_{SM} | Pulsed Source Current (Body Diode) ① | --- | --- | 8.4 | | |
| V_{SD} | Diode Forward Voltage | --- | --- | 1.8 | V | $T_J=25^\circ\text{C}, I_S=2.1A, V_{GS}=0V$ ④ |
| t_{rr} | Reverse Recovery Time | --- | 480 | 720 | ns | $T_J=25^\circ\text{C}, I_F=4.1A$ |
| Q_{rr} | Reverse Recovery Charge | --- | 1.8 | 2.7 | μC | $di/dt=100A/\mu s$ ④ |
| t_{on} | Forward Turn-On Time | Intrinsic turn-on time is negligible (turn-on is dominated by L_S+L_D) | | | | |

Notes:

- ① Repetitive rating; pulse width limited by max. junction temperature (See Figure 11)
- ② $V_{DD}=50V$, starting $T_J=25^\circ\text{C}$, $L=102\text{mH}$, $R_G=25\Omega$, $I_{AS}=2.1A$ (See Figure 12)
- ③ $I_{SD}\leq 4.1A$, $di/dt\leq 100A/\mu s$, $V_{DD}\leq 600$, $T_J\leq 150^\circ\text{C}$
- ④ Pulse width $\leq 300\mu s$; duty cycle $\leq 2\%$
- ⑤ $t=60s$, $f=60\text{Hz}$






Fig 3. Typical Transfer Characteristics




Fig 4. Normalized On-Resistance Vs. Temperature

IRFIBE30GPbF

International
IR Rectifier




Fig 5. Typical Capacitance Vs. Drain-to-Source Voltage




Fig 6. Typical Gate Charge Vs. Gate-to-Source Voltage




Fig 7. Typical Source-Drain Diode Forward Voltage




Fig 8. Maximum Safe Operating Area




Fig 12a. Unclamped Inductive Test Circuit




Fig 12b. Unclamped Inductive Waveforms




Fig 12c. Maximum Avalanche Energy Vs. Drain Current




Fig 13a. Basic Gate Charge Waveform






Fig 13b. Gate Charge Test Circuit

Peak Diode Recovery dv/dt Test Circuit



- * Reverse Polarity for P-Channel
- ** Use P-Channel Driver for P-Channel Measurements




*** $V_{GS} = 5.0V$ for Logic Level and 3V Drive Devices

Fig -14 For N Channel HEXFETS

TO-220 Full-Pak Package Outline

Dimensions are shown in millimeters (inches)




- NOTES:
- 1.0 DIMENSIONING AND TOLERANCING PER ASME Y14.5 M- 1994.
 - 2.0 DIMENSIONS ARE SHOWN IN MILLIMETERS [INCHES].
 - 3.0 LEAD DIMENSION AND FINISH UNCONTROLLED IN L1.
 - 4.0 DIMENSION D & E DO NOT INCLUDE MOLD FLASH. MOLD FLASH SHALL NOT EXCEED 0.005" (0.127) PER SIDE. THESE DIMENSIONS ARE MEASURED AT THE OUTERMOST EXTREMES OF THE PLASTIC BODY.
 - 5.0 DIMENSION b1 APPLY TO BASE METAL ONLY.
 - 6.0 STEP OPTIONAL ON PLASTIC BODY DEFINED BY DIMENSIONS u & v.
 - 7.0 CONTROLLING DIMENSION : INCHES.

| SYMBOL | DIMENSIONS | | | | NOTES | LEAD ASSIGNMENTS |
|--------|-------------|-------|-----------|-------|-------|------------------|
| | MILLIMETERS | | INCHES | | | |
| | MIN. | MAX. | MIN. | MAX. | | |
| A | 4.57 | 4.83 | 0.180 | 0.190 | | |
| A1 | 2.57 | 2.83 | 0.101 | 0.114 | | |
| A2 | 2.51 | 2.85 | 0.099 | 0.112 | | |
| b | 0.622 | 0.89 | 0.024 | 0.035 | | |
| b1 | 0.622 | 0.858 | 0.024 | 0.033 | 5 | |
| b2 | 1.229 | 1.400 | 0.048 | 0.055 | | |
| b3 | 1.229 | 1.400 | 0.048 | 0.055 | | |
| c | 0.440 | 0.629 | 0.017 | 0.025 | | |
| c1 | 0.440 | 0.584 | 0.017 | 0.023 | | |
| D | 8.65 | 9.80 | 0.341 | 0.386 | 4 | |
| d1 | 15.80 | 16.12 | 0.622 | 0.635 | | |
| d2 | 13.97 | 14.22 | 0.550 | 0.560 | | |
| d3 | 12.30 | 12.92 | 0.484 | 0.509 | | |
| d4 | 8.64 | 9.91 | 0.340 | 0.390 | | |
| E | 10.36 | 10.63 | 0.408 | 0.419 | 4 | |
| e | 2.54 BSC | | 0.100 BSC | | | |
| L | 13.20 | 13.73 | 0.520 | 0.541 | | |
| L1 | 3.10 | 3.50 | 0.122 | 0.138 | 3 | |
| n | 6.05 | 6.15 | 0.238 | 0.242 | | |
| phi P | 3.05 | 3.45 | 0.120 | 0.136 | | |
| u | 2.40 | 2.50 | 0.094 | 0.098 | 6 | |
| v | 0.40 | 0.50 | 0.016 | 0.020 | 6 | |
| phi 1 | 3° | 7° | 3° | 7° | | |
| phi 2 | 45° | 45° | | | | |

TO-220 Full-Pak Part Marking Information

EXAMPLE: THIS IS AN IRF1840G
 WITH ASSEMBLY
 LOT CODE 3432
 ASSEMBLED ON WW 24 1999
 IN THE ASSEMBLY LINE "K"

Note: "P" in assembly line position indicates "Lead-Free"



Data and specifications subject to change without notice.



Notice

The products described herein were acquired by Vishay Intertechnology, Inc., as part of its acquisition of International Rectifier's Power Control Systems (PCS) business, which closed in April 2007. Specifications of the products displayed herein are pending review by Vishay and are subject to the terms and conditions shown below.

Specifications of the products displayed herein are subject to change without notice. Vishay Intertechnology, Inc., or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document. Except as provided in Vishay's terms and conditions of sale for such products, Vishay assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of Vishay products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Vishay for any damages resulting from such improper use or sale.

International Rectifier®, IR®, the IR logo, HEXFET®, HEXSense®, HEXDIP®, DOL®, INTERO®, and POWIRTRAIN® are registered trademarks of International Rectifier Corporation in the U.S. and other countries. All other product names noted herein may be trademarks of their respective owners.