



NTE397

Silicon PNP Transistor

Power Amplifier & High Speed Switch (Compl to NTE396)

Absolute Maximum Ratings:

Collector-Emitter Voltage, V_{CEO}	300V
Collector-Base Voltage, V_{CBO}	350V
Emitter-Base Voltage, V_{EBO}	6V
Continuous Collector Current, I_C	1A
Base Current, I_B	500mA
Total Device Dissipation ($T_C = +25^\circ\text{C}$), P_D	10W
Derate Above 25°C	57mW/ $^\circ\text{C}$
Operating Junction Temperature Range, T_J	-65° to +200° $^\circ\text{C}$
Storage Temperature Range, T_{stg}	-65° to +200° $^\circ\text{C}$
Thermal Resistance, Junction-to-Case, R_{thJC}	17.5°C/W
Thermal Resistance, Junction-to-Ambient, R_{thJA}	150°C/W

Electrical Characteristics: ($T_A = +25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
OFF Characteristics						
Collector-Emitter Sustaining Voltage	$V_{CEO(sus)}$	$I_C = 50\text{mA}$, $I_B = 0$, Note 1	300	—	—	V
Collector Cutoff Current	I_{CBO}	$V_{CB} = 280\text{V}$, $I_E = 0$	—	—	50	μA
Emitter Cutoff Current	I_{EBO}	$V_{EB} = 6\text{V}$, $I_C = 0$	—	—	20	μA
ON Characteristics						
DC Current Gain	h_{FE}	$I_C = 50\text{mA}$, $V_{CE} = 10\text{V}$	30	—	120	
Small-Signal Characteristics						
Output Capacitance	C_{obo}	$V_{CB} = 10\text{V}$, $I_E = 0$, $f = 1\text{MHz}$	—	—	15	pF
Input Capacitance	C_{ibo}	$V_{CB} = 5\text{V}$, $I_C = 0$, $f = 1\text{MHz}$	—	—	75	pF
Small-Signal Current Gain	h_{fe}	$I_C = 10\text{mA}$, $V_{CE} = 10\text{V}$, $f = 1\text{MHz}$	25	—	—	
Real Part of Input Impedance	$\text{Re}(h_{ie})$	$V_{CE} = 10\text{V}$, $I_C = 5\text{mA}$, $f = 1\text{MHz}$	—	—	300	Ω

Note 1. Pulse Test; Pulse Width $\leq 300\mu\text{s}$, Duty Cycle $\leq 2\%$.

CAUTION: The sustaining voltage ***must not*** be measured on a curve tracer.

