

# Model #: ULTRABLOK

### Isobar Surge Suppressor - Direct plug-in surge, spike and line noise protection



#### **Highlights**

- 2 (15A) outlets/direct plug-in
- 1410 joule rating
- All-metal housing with LEDs
- \$10,000 Ultimate Lifetime Insurance (USA, Puerto Rico & Canada only)

#### **Description**

For more than 20 years, America's leading companies have trusted Tripp Lite's Isobar Premium surge and noise suppressors to protect sensitive computer, networking and telecom equipment. With more than 15 million satisfied customers, the ISOBAR remains the world's #1 selling premium surge suppressor. Loaded with a generous combination of high-quality components, near indestructible all-metal case and unique noise filtration system, Isobars offer the highest levels of protection. Robust surge suppression circuits with sine wave tracking offer extreme levels of protection against the heaviest surge conditions. Isobar's unique protection system combines large torroidal chokes, HF/VHF capacitors and multiple metal oxide varistors that remove high-level surges and EMI/RFI interference. UltraBlok 428 offers 2 outlets arranged with standard wall socket spacing in a cordless direct plug-in format. Mounting tabs allow permanent connection via duplex switchplate screw. Surge suppression rated at 1410 joules/48,000 amps offers high-grade protection. Diagnostic LEDs confirm power availability, line fault and protection status. Lifetime warranty with \$10,000 Ultimate Lifetime connected equipment Insurance (USA & Canada Only).

PLUG/OUTLETS: Input-NEMA 5-15P; Output-2 NEMA5-15R

ELECTRICAL: 120V AC, 50/60Hz, 15A (Requires NEMA 5-15R wall receptacle)

SUPPRESSION: AC: 140V RMS Clamping/1410 joules/48,000 amps

FORMAT: Direct plug-in, receptacle mount form factor

#### Applications

Ideal for premium AC protection for personal computers with peripherals, network and CAD/CAM/CAE workstations, internetworking
accessories, telecommunications systems, point of sale equipment, audio/video and home theater systems in any home, office or industrial
application.

Package Includes

Instruction manual and warranty information

## **Specifications**

OVERVIEW		
Intended Application	Home/Office, Travel	
OUTPUT		
Frequency compatibility	50 / 60 Hz	
Output watts	1800	
Output volt amp capacity (amps)	15	
Outlet quantity / type	2 NEMA 5-15R	
INPUT		
Recommended Electrical Service	120V (110-125V)	
Input connection type	NEMA 5-15P	
Input cord length details	Direct plug-in	
Voltage compatibility (VAC)	120	
LEDS ALARMS & SWITCHES		
Diagnostic LEDs	PROTECTION PRESENT (green), LINE FAULT (red) and LINE OK (green)	
SURGE / NOISE SUPPRESSION		
AC suppression joule rating	1410	
AC suppression response time	NM = 0 ns. CM =	
Protection modes	Includes full normal mode (H-N) and common mode (N-G / H-G) line surge suppression	
Clamping voltage (RMS)	140	
AC suppression surge current rating	48,000 amps	
AC suppression components used	Metal oxide varistors, toroidal balanced chokes and VHF capacitors	
Safe thermal fusing	Prevents unsafe conditions during extreme extended overvoltages and catastrophic occurences	
EMI / RFI filtering	40-80 dB	
Immunity	Conforms to IEE 587 / ANSI C62.41	
DATALINE SURGE SUPPRESSION		
Cable (Coax) Protection	No	
Network (Ethernet) Protection	No	
PHYSICAL		
Shipping weight (lbs)	1	
Unit Dimensions (HWD/in)	4 x 2.5 x 2.5	

Shipping Dimensions (HWD/in)	5 x 3.75 x 2.5	
Unit weight (Ibs)	.8	
Material of construction	Metal	
Housing Color	Black	
Receptacle Color	Black	
Style	Direct Plug-in	
Form factors supported	Direct plug-in format with retaining bracket supports wall mounting directly to a standard AC wall socket	
SPECIAL FEATURES		
Appearance	Attractive, all-black color scheme	
CERTIFICATIONS		
UL1449 3rd Edition (AC Suppression)	UL1449 3rd EDITION	
UL1283 (EMI Filter)	UL1283	
cUL / CSA (Canada)	cUL	
Approvals	Exceeds IEEE 587 category A&B specifications	
WARRANTY		
Product Warranty Period (U.S., Canada & Puerto Rico)	Lifetime limited warranty	
Connected Equipment Insurance (U.S., Canada & Puerto Rico)	\$10,000 Ultimate Lifetime Insurance	

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModeIID=3980.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.