

Features

- Subminiature in SMT
- 7.36 mm seated height
- Distortion of only 0.015 %
- Vacuum encapsulated
- UL60950 certified
- RoHS compliant*

Applications

- Modems (V32)
- Laptop Computers
- Telecommunications
- Instrumentation

SM-LP-5001 Series -Surface Mount Line Matching Transformers

Electrical Specifications

Nominal Impedance	600 Ω
Turns Ratio	1:1
Insertion Loss	2.0 dB max. at 2 kHz
Frequency Response	±0.25 dB max. 200-4 kHz
Return Loss	24 dB min. 200-4 kHz*
Balance	80 dB min.
Distortion	-76 dB max.
	@ 600 Hz, -10 dBm
Dielectric Strength	2000 VRMS for 1 min.
Insulation Resistance	100 MΩ @ 500 V
DC Resistance**	
Primary	115 Ω ±15 %
Secondary	115 Ω ±15 %
Shunt Inductance	3.8 H min.
Shunt Loss	7500 Ω min.
Leakage Inductance6 mH typ. @ 1 kHz
Power Level	10 dBm
Operating Temperature	-20 °C to +85 °C
Storage Temperature	-40 °C to +85 °C


Materials

Terminal Plating AgSn


*For use with recommended circuit (BS6305 impedance Class A non-speech or Class B speech).

**SM-LP-5001 is symmetrical, meaning there is no real primary nor secondary winding.

Product Dimensions



Suggested PCB Layout



DIMENSIONS: $\frac{\text{MM}}{\text{(INCHES)}}$

LEAD COPLANARITY: $\frac{0.15}{(0.006)}$ MAX.

UNLESS OTHERWISE SPECIFIED, TOLERANCE: $\frac{\pm 0.25}{(0.010)}$ MAX.

How To Order


SM-LP-5001

Model _____

Packaging _____

Blank = Packaged in tubes
E = Tape and reel (400 pcs. per reel)

Schematic



REV. 04/11

*RoHS Directive 2002/95/EC Jan 27, 2003 including Annex.
Specifications are subject to change without notice.
Customers should verify actual device performance in their specific applications