


# General Purpose Carbon Film Resistors

## CF Series

- High stability performance
- Only available as Lead Free
- Auto sequencing/insertion compatible
- Ideal for commercial/industrial applications



## Electrical Data

		Tested per MIL-STD-202		
		CF 1/8	CF 1/4	CF 1/2
Power Rating (watts) at 70°C		1/8	1/4	1/2
Derated to 0 Load at		155°C		
Maximum Working Voltage		200V	250V	350V
Operating Temperature Range		-55°C to +155°C		
Resistance Range	(±5%)	1.0 Ω - 22 MΩ		
	(±2%)	10 Ω - 1 MΩ	10 Ω - 4.7 MΩ	10 Ω - 4.7 MΩ

## Environmental Data

	CF 1/8	CF 1/4	CF 1/2
Moisture Resistance	<100 K ± (3% + 0.05 Ω)		
	>100 K ± (5% + 0.05 Ω)		
Thermal Shock	±0.5%		
Load life at 70°C - 1000 hours	<100 K ± (2% + 0.05 Ω)		
	<100 K ± (3% + 0.05 Ω)		
Shock and Vibration	±0.2%		
Resistance to Soldering Heat	±0.5%		
Terminal Strength	±0.5%		
Dielectric Withstand Voltage	300 volts RMS min.	500 volts RMS min.	700 volts RMS min.
Maximum Pulse Voltage	400V	600V	700V
Insulation Resistance	10,000 meg min.		
Voltage Coefficient	-10 ppm/Vmax.		
Short Time Overload	±0.75%		

### General Note

IRC reserves the right to make changes in product specification without notice or liability. All information is subject to IRC's own data and is considered accurate at time of going to print.

Wire and Film Technologies Division • 4222 South Staples Street • Corpus Christi Texas 78411 USA  
Telephone: 361 992 7900 • Facsimile: 361 992 3377 • Website: www.irctt.com




A subsidiary of  
TT electronics plc

CF Series Issue Sept 2009 Sheet 1 of 3


# General Purpose Carbon Film Resistors

## Physical Data



Dimensions (inches and (mm))			
Dimension	CF 1/8	CF 1/4	CF 1/2
A	1.10 ± .08 (28.0 ± 2.0)		
B	0.13 + .01/-0.00 (3.2 + 0.2/-0.0)	0.24 ± .01 (6.0 ± 0.3)	0.33 ± .02 (8.5 ± 0.5)
C	0.018 ± .001 (0.45 ± 0.02)	0.022 ± .001 (0.55 ± 0.03)	0.026 ± .002 (0.65 ± 0.05)
D	0.07 ± .01 (1.8 ± 0.15)	0.09 ± .01 (2.3 ± 0.2)	0.11 ± .01 (2.8 ± 0.3)

## Construction



### 1. COLOR BANDS.

The resistors are permanently color banded for resistance value and tolerance in accordance with EIA specifications.

### 2. HELIXING.

The units are helixed to a predetermined base to final value ratio to obtain the best TCR, noise and stability characteristics.

### 3. FILM.

Carbon-film resistors have a homogeneous film of pure carbon deposited by a pyrolytic process at carefully controlled temperatures.

### 4. SUBSTRATES.

The substrates are of a proprietary non alkaline ceramic, prepared and processed under exacting conditions to guarantee the utmost in uniformity and surface characteristics.

### 5. INSULATION.

The resistors are coated with multiple layers of a baked-on fire-retardant synthetic resin which provides the units with a high degree of mechanical and electrical protection in the most adverse operating conditions.

### 6. TERMINATIONS.


Positive contact is provided to the resistance element by precision-made end caps. The lead wires are attached by using proprietary welding techniques.

# General Purpose Carbon Film Resistors




## Performance Curves


Temperature Coefficient (Typical)



Derating Curve (Typical)



Current Noise (Typical)



## Ordering Data

