


# PCB DIN Receptacle

161-0505-E

KOBI CONN

PCB DIN Receptacles



## SPECIFICATIONS

<b>Type:</b>	PCB Mount DIN, Shielded
<b>Rating:</b>	2A/100VAC, 1A/24VDC
<b>Contact Resistance:</b>	20mΩ max.; <100mΩ After 5000 Cycles
<b>Insulation Resistance:</b>	100MΩ min. @ 500VDC
<b>Dielectric Strength:</b>	500VAC for 1 Minute
<b>Insertion Force:</b>	5.0Kg max.
<b>Extraction Force:</b>	1~3.5Kg
<b>Mates With Plug ø:</b>	.520±.008", .536±.004"
<b>Dimension Tolerance:</b>	±.008"
<b>Marking:</b>	U.E.C.
<b>Body:</b>	Valox 420-SEO with 30% Glass Fiber
<b>Contact:</b>	Tin Plated Brass
<b>Insulator:</b>	Bakelite
<b>Shielding Terminal:</b>	Tin Plated Phosphor Bronze
<b>RoHS Compliant</b>	

Date Last Revised: 1-16-08

Available from Mouser Electronics  
1-800-346-6873 / [www.mouser.com](http://www.mouser.com)

KC-301191

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.

161-0505-E