



Recommended PCB Layout (Bottom View)

Materials and Finish

Housing: High Temperature Thermoplastic, 15% Glass Filled Orange (Pantone 284C) Color UL 94V-0 Rated

Terminals:
Pin 1: Brass, Matte Tin Plated
Pin 2, 5: Phosphor Bronze Matte Tin Plated

Electrical Characteristics

Contact Resistance:
Before Test: 50 milliohms Max.
After Durability Test: 100 milliohms Max.

Insulation Resistance:
More than 100 Megohms at 500V DC

Dielectric Strength:
500V AC RMS for 1 minute

Operating Temp:
-25°C to +85°C

Mechanical Characteristics

Insertion Force:
0.4kg - 3.0kg

Extraction Force:
0.3kg - 3.0kg

Durability: 5000 mating cycles



Tolerances
X.X ± 0.3
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A0	9/22/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	07/14/05
A1	6/2/06	Release Drawing	H. MA	N/A		
B1	08/12/09	ECO #09-039	S. Vlen	H. MA		
B2	11/10/10	ECO #10-078	S. Vlen	H. MA		

STX-3120-3B-284C

Stereo Jack, 3 Position, RoHS Compliant
Meets PC99 Spec, Light Blue Color

