


- Open insulator.
- Sockets are XY stackable.
- Stamped and formed DIP sockets with a dual beam contact for positive retention (Phosphor Bronze).
- Stand-offs aid the cooling process and facilitate cleaning and soldering.
- Insulator material is PBT.



Total number of pins				Quantity per box	<h2 style="text-align: center;">Ordering Information</h2>				
	A	B	C						
6	0.3	0.3	0.4	8,000	110-90-306-00-000000				
8	0.4	0.3	0.4	6,000	110-90-308-00-000000				
14	0.7	0.3	0.4	3,400	110-90-314-00-000000				
16	0.8	0.3	0.4	3,000	110-90-316-00-000000				
18	0.9	0.3	0.4	2,600	110-90-318-00-000000				
20	1.0	0.3	0.4	2,400	110-90-320-00-000000				
24	1.2	0.3	0.4	2,000	110-90-324-00-000000				
28	1.4	0.3	0.4	1,700	110-90-328-00-000000				
24	1.2	0.6	0.7	2,000	110-90-624-00-000000				
28	1.4	0.6	0.7	1,700	110-90-628-00-000000				
32	1.6	0.6	0.7	1,500	110-90-632-00-000000				
40	2.0	0.6	0.7	1,200	110-90-640-00-000000				
48	2.4	0.6	0.7	1,000	110-90-648-00-000000				
PLATING CODE =								90	
Contact								200μ" Sn/Pb	

Downloaded from Elcodis.com electronic components distributor