



- NOTE:
1. OUTER MOLDED WITH BLK PVC RESIN 887800019
 2. ALL COMPONENT MUST MEET RoHS REQUIREMENT.

SHELL	BRAID WIRE	H	TERMINAL 887809090(24AWG)	L	QTY.
4	AWG24 BLACK	G	USB CONNECT(FEMALE) ,887899591		1
3	AWG28 GREEN	F	USB 2.0 #28/#24 OD=4.3 black,172000467	ZM Ref.	
2	AWG28 WHITE	E	COPPER FOIL 887801083		1
1	AWG24 RED	D	TERMINAL 887809091 (AWG28)		2
P1	WIRE COLOR	C	REAR SHELL,887809084		1
		B	FRONT SHELL ,887809083		1
		A	CRIMP HOUSING 887809086		1

ENTER DESCRIPTION EC NO: DG2006-0078 DRW:PHZHU CHKD: APPR:DLUO	DESCRIPTION 2005/10/15 2005/10/19 2005/10/20	QUALITY SYMBOLS ▽=0 ▽=2	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
			mm	INCH	---	METRIC	☉		
1	DESCRIPTION		4 PLACES	±---	±---	DRAWN BY PHZHU	DATE 2005/10/13	TITLE USB EXTENDER (M TO F) TYPE A/A BLACK 6.6' ASSY	
			3 PLACES	±---	±---	CHECKED BY ZXDENG	DATE 2005/10/13		
			2 PLACES	±---	±---	APPROVED BY DQLUO	DATE 2005/10/13		
			1 PLACE	±---	±---	MATERIAL NO. 688060013	DATE 2005/10/13		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			ANGULAR ±1/2°		MOLEX INCORPORATED		DOCUMENT NO. SD-68806-013	SHEET NO. 1 OF 1	

ib_frame_A4_P_ME_T
Rev. D 2004/04/02