



## **FEATURES:**

• Bantam plugs are molded directly to the cable for optimum durability

## **MATERIALS:**

Bantam Plug: Body – Brass, Insulation – PVC, Color: Black
Audio Cable: Two Conductor Twisted Pair With Spiral Shield, Color: Gray Capacitance: 40 pF/Ft. Conductors: 22 AWG, Stranding: 7 x 30 Jacket: PVC, O.D. .180" (4,6mm) Nom., Marking: "POMONA 4279-XX"
Finish: 4279N Brass nickel plated

## **RATINGS:**

Operating Temperature: +50°C (+122°F) Operating Voltage: 300 VRMS

## **ORDERING INFORMATION:** Model 4279-XX and 4279N-XX

XX = Cable Length, Standard Lengths: 12" (30,5 cm), 24" (61 cm), 36" (91,44cm), 48" (121,92cm), 60" (152,4cm) Additional lengths can be quoted upon requested.

Ordering Example: 4279-12, Cable length is 12" with non-plated Bantum connector 4279N-24, Cable length is 24 with brass nickel plated Bantum connector

All dimensions are in inches. Tolerances (except noted):  $.xx = \pm .02$ " (,51 mm),  $.xxx = \pm .005$ " (,127 mm). All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

5/31/02 SY/EH/LS
Last saved by PN
S:\Engineering\Release\DataSheet\\HukeDataSheet\\4279 78N 1 02.doc

PomonaACCESS 90344 (800) 444-6785 or (425) 446-6010 More drawings available at www.pomonaelectronics.com Page 1 of 1