





# Heyco® Straight-Thru Strain Relief Bushings

For Flat Cables, With Flex-Protecting Internal Radii and Extra Body Length

- Sizes for thin .040" (1,0 mm) panel available: SR 4A-6 & SR 3A-4. See charts for details.
- Protects the lifeline of your electric/electronic products by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cable at panel entry points.
- Standardize panel design! Fill unused SR mounting holes with Heyco Double "D" Plugs, page 3-23.
- See page 3-24, 3-25, and 3-26 for SR hole punches and assembly tools.
- See page 3-12 for Quick Specs.



\*To install strain reliefs for .040" (1,0 mm) maximum panel thickness, use Part #0021 (No. R-291) Hand Pliers.

WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C BODY LENGTH	
UL Type Designation	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Maximum Panel Thickness				Black	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.				
SPT-1	18/3	.12x.30	3,0x7,6										
SPT-2 & HPN	18/2	.15x.28	3,8x7,1	.500	12,7	.465	11,8	.040*	1,0	<b>1181</b>	SR 4A-6	.546	13,9
Same as SR-4A-6 above except								.062	1,6	<b>1187</b>	SR 4N-6	.546	13,9
Same as SR-4A-6 above except								.100	2,5	<b>1190</b>	SR 4K-6	.546	13,9

Standard colors black. Consult Heyco for white and other colors.

## For Flat Cables

WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C BODY LENGTH	
UL Type Designation	AWG/ Conductors	Approximate Size		A Mounting Hole Dia.		B To Prevent Rotation		Maximum Panel Thickness				Black	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.				
CLOCK	20/2	.09x.18	2,3x4,6	.375	9,5	.345	8,8	.062	1,6	<b>1017</b>	SR 2P-4	.406	10,3
SPT-1	18/2	.11x.21	2,8x5,3										
Same as SR 2P-4 above except								.125	3,2	<b>1034</b>	SR 2L-1	.406	10,3
SPT-1	18/2	.12x.22	3,0x5,6	.437	11,1	.390	9,9	.040*	1,0	<b>1074</b>	SR 3A-4	.406	10,3
Same as SR 3A-4 above except								.062	1,6	<b>1077</b>	SR 3P-4		
								.100	2,5	<b>1104</b>	SR 3W-1	.406	10,3
								.156	4,0	<b>1094</b>	SR 3L-1		
SPT-1	18/2	.12x.22	3,0x5,6	.500	12,7	.445	11,3	.100	2,5	<b>1130</b>	SR 4P-4	.440	11,2
SPT-1	18/3	.12x.30	3,0x7,6	.500	12,7	.465	11,8	.062	1,6	<b>1120</b>	SR 4N-4	.406	10,3
HPN	18/2	.15x.28	3,8x7,1										
Same as SR 4N-4 above except								.100	2,5	<b>1117</b>	SR 4K-4	.406	10,3
								.156	4,0	<b>1127</b>	SR 4L-4	.406	10,3
SPT-1	18/3	.12x.30	3,0x7,6										
SPT-2 & HPN	18/2	.15x.28	3,8x7,1	.500	12,7								
HPN	18/3	.15x.34	3,8x8,6			.460	11,7	.095	2,4	<b>1114</b>	SR 4K-1	.500	12,7
SPT-2 & HPN	16/2	.16x.30	4,1x7,6	.500-.515	12,7-13,1								
Same as SR 4K-1 above except								.187	4,7	<b>1124</b>	SR 4L-1	.500	12,7
SPT-3	18/2	.19x.35	4,8x8,9										
	16/2	.20x.37	5,1x9,4										
SPT-2	18/3	.15x.40	3,8x10,2	.562	14,3	.530	13,5	.062	13,5	<b>1170</b>	SR 5KN-4	.609	15,5
SPT-2	16/3	.16x.41	4,1x10,4										
Same as SR 5KN-4 above except								.125	3,2	<b>1167</b>	SR 5K-4	.609	15,5

Standard color black. Consult Heyco for white and other colors.