



Heyco® Straight-Thru Strain Relief Bushings


For Round Cables




WILL FIT THESE CABLES				PANEL DIMENSIONS						PART NO.	DESCRIPTION	C Body Length													
UL Type Designation	AWG/ Conductors	Approximate Diameter		A		B		Maximum Panel Thickness ¹				in.	mm.												
		in.	mm.	Mounting Hole Dia. in.	mm.	To Prevent Rotation in.	mm.	in.	mm.																
SJT	18/4 14/3	.360 .370	9,1 9,4																						
S & ST	18/2 18/3 16/2	.390 .405 .405	9,9 10,3 10,3	.750	19,0	.660	16,8	.062	1,6	1244	SR 7N-2	.750	19,1												
	16/3	.430	10,9											.750- .781	19,0- 19,8										
	Same as SR 7N-2 above except								.125					3,2	1237	SR 7P-2	.750	19,1							
SJ, SJT & SJO	16/2 18/3 14/2 16/3 18/4	.325 .330 .350 .355 .360	8,3 8,4 8,9 9,0 9,1	.875	22,2	.770	19,6	.125	3,2	1240	SR 7K-2	.750	19,1												
	Same as SR 7K-2 above except													See Schematic				1271	SR 7KR-2	.750	19,1				
	SJT	14/3 12/3	.370 .425											9,4 10,8											
		S & ST	18/2 18/3 16/2 16/3											.390 .405 .405 .430	9,9 10,3 10,3 10,9	.875	22,2	.770	19,6	.125	3,2	1247	SR 7W-2	.750	19,1
	Same as SR 7W-2 above except																								
SJT	12/3		.425- .475	10,8- 12,1	.875	22,2	.840	21,3	.125	3,2	1497	SR 31-2	.812	20,6											
S & ST	14/2 14/3 12/2	.530 .560 .600	13,5 14,2 15,3	.875	22,2	.840	21,3	.062	1,6	1254	SR 8N-2	.828	21,0												
	Same as SR 8N-2 above except																	.125 .187	3,2 4,8	1260 1274	SR 8P-2 SR 8L-1	.812	20,6		
S	12/2 12/3	.600 .635	15,2 16,1	1.093 1.125	27,7 28,6	1.000	25,4	.281	7,1	1287	SR 9P-2	1.00	25,4												
	10/2	.640	16,3	1.093	27,7																				
S, ST & SO	10/3	.690	17,5	1.187	28,6																				

- Sizes SR7 to SR9 for mounting hole diameters from .750" (19,0 mm) to 1.187" (28,6 mm).
- Protects the lifeline of your electric/electronic products by absorbing the forces of pull, push, and twist that may be exerted on the flexible power cord.
- Securely anchors, insulates, and protects cables at panel entry points.
- Standardize panel design! Fill unneeded SR mounting holes with Heyco Double "D" Plugs, page 3-23.
- Sizes for thin .062" (1,6 mm) panel available:
SR 7N-2
SR 8N-2
See chart for details.
- See pages 3-24, 3-25 and 3-26 for SR hole punches and assembly tools.
- See page 3-13 for Quick Specs.

Standard color black. Consult Heyco for white and other colors.
¹Maximum Panel Thickness-Part has additional clearance.



FOR SR-7KR-2 ONLY



STANDARD MOUNTING HOLES

