



Heyco® Glossy Plugs


- Closes unneeded panel openings.
- Smooth, glossy head provides easy glide and shiny finish.
- Multiple sizes for use in .187" (4,7 mm) to 2.00" (50,8 mm) diameter holes.
- Locks firmly in panel up to .125" (3,2 mm) thick.
- Quick and easy installation.

PANEL DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS			
Maximum Thickness		Mounting Hole Diameter		Black	White		A Head Diameter		B Overall Height	
in.	mm.	in.	mm.			in.	mm.	in.	mm.	
.062	1,6	.187	4,7	2590*	2591*	DP-187**	.250	6,4	.234	5,9
.062	1,6	.250	6,4	2600*	2601*	G-250	.312	7,9	.312	7,9
.062	1,6	.312	7,9	2610*	2611*	G-312	.375	9,5	.312	7,9
.125	3,2	.375	9,5	2620	2621	G-375	.468	11,9	.406	10,3
.125	3,2	.437	11,1	2630	2631	G-437	.531	13,5	.406	10,3
.125	3,2	.500	12,7	2640	2641	G-500	.563	14,3	.406	10,3
.125	3,2	.562	14,3	2650	2651	G-562	.656	16,7	.406	10,3
.125	3,2	.625	15,9	2660	2661	G-625	.734	18,6	.406	10,3
.125	3,2	.750	19,1	2680	2681	G-750	.859	21,8	.406	10,3
.125	3,2	.875	22,2	2700	2701	G-875	.953	24,2	.453	11,5
.125	3,2	1.000	25,4	2710	2711	G-1000	1.125	28,6	.453	11,5
.125	3,2	1.093	27,8	2720	2721	G-1093	1.218	30,9	.453	11,5
		1.125	28,6							
.125	3,2	1.187	30,1	2730	2731	G-1187	1.312	33,3	.453	11,5
.125	3,2	1.375	34,9	2760	2761	G-1375	1.486	37,7	.453	11,5
.125	3,2	1.500	38,1	2770	2771	G-1500	1.609	40,8	.453	11,5
.125	3,2	1.750	44,4	2780	2781	G-1750	1.875	47,6	.453	11,5
.125	3,2	2.000	50,8	2795	2796	G-2000	2.127	54,0	.453	11,5



Standard color black. Consult Heyco for other colors.
Locking fingers in fractional increments up to the maximum panel thickness.

*Depicts single panel thickness design.

**Domed glossy finished head tapers to a thin edge.



SINGLE PANEL THICKNESS DESIGN*



MULTIPLE PANEL THICKNESS DESIGN

Quick Specs

Material Certifications



6/6 Nylon
Recognized under the Component Program of Underwriters' Laboratories, File E51579



Certified by Canadian Standards Association, File LR8919

Flammability Rating

94V-2

Material Temperature Index

257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)