DESC	2 INSULATOR 1 RONY			6 LOCK WASHER	7 FERRULE	α	1.60 [.063]→		8 HEX	1.70 [.067] +-		9.90 [.39 5.50 [.25	-					
MATERIAL	TEFLON BRASS	BER. COPPER	SILICONE	BRASS	BRASS		Ŧ	ø6.50 [ø.256]		<u>+</u>	-6.60 [.2]							
QTY DO NOT SCALE	NATURAL 1 .020 315 ± 0.007" GOI D 1 .315 - 1.180 = ± 0.015"	1 UNLESS OTHERWISE		GOLD 1 0.5 - 8mm ± 0.20mm	GOLD UNLESS OTHERWISE SPECIFIED	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN MILLINETERS, DIMENSIONS IN [] JARE IN INCHES AND FOR CUSTOMER REFERENCE ONLY.				10.50 [.414]	[.260]-		1/4-36UNS-2A					
000 FILE C:/132/132105.DWG	-			CHECKED	E. DRAWN G.R.S. 01/29/03					748]			-2.24 [.088] -3.20 [.126]	4IN.		СС	ВО	REV.
dwg. NO. 132105.DWG	PART NO.	.085",	IA DIRECT	PART DESCRIPTION			1. CONTAC 2. MAX. P <i>4</i>	RECOMMENDED CABLE STRIPPING DIMS.			← 6.60 [.260] +		-1.27 [.050]		01/29/03		01/12/98 ADI	DATE
REV. D SIZE A SCALE NA	132105	.086" SEMI-RIGID CABLE)	R BULKHEAD			nol Connov	re: 1. CONTACT PIN TO SOLDER 2. MAX. PANEL THICKNESS = 2.4mm	JED CABLE G DIMS.			<u>→</u> <u>→</u> .50 [.020]		60 [.023]		UPDATE DRAWING FORMAT	MODIFY 'O'-RING DIMENSIONS	ADD INSULATOR/ STRIPPING DIM'S	DESCRIPTION