



Heyco® Rubber Grommets

Mounting Diameter: 0.875" to 1.250"

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63.5 mm) diameter and panel thicknesses from .063" (1,6mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height
in.	mm.	in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.063	1,6	.875	22,2	G1215	RG 875-20-2	.625	15,9	1.125	28,6	.313	8,0
.125	3,2	.875	22,2	G1218	RG 875-20-4	.625	15,9	1.125	28,6	.375	9,5
.188	4,8	.875	22,2	G1219	RG 875-20-6	.625	15,9	1.125	28,6	.438	11,1
.250	6,4	.875	22,2	G1220	RG 875-20-8	.625	15,9	1.125	28,6	.500	12,7
.313	8,0	.906	23,0	G1224	RG 906-20-10	.625	15,9	1.125	28,6	.625	15,9
.375	9,5	.968	24,6	G1232	RG 968-22-12	.688	17,5	1.313	33,4	.625	15,9
.063	1,6	1.000	25,4	G1242	RG 1000-12-2	.375	9,5	1.250	31,8	.250	6,4
.125	3,2	1.000	25,4	G1244	RG 1000-12-4	.375	9,5	1.313	33,4	.375	9,5
.063	1,6	1.000	25,4	G1246	RG 1000-16-2	.500	12,7	1.250	31,8	.250	6,4
.125	3,2	1.000	25,4	G1247	RG 1000-16-4	.500	12,7	1.250	31,8	.313	8,0
.266	6,8	1.000	25,4	G1248	RG 1000-16-8	.500	12,7	1.375	34,9	.500	12,7
.375	9,5	1.000	25,4	G1249	RG 1000-18-12	.563	14,3	1.250	31,8	.625	15,9
.063	1,6	1.000	25,4	G1252	RG 1000-22-2	.688	17,5	1.313	33,4	.375	9,5
.078	2,0	1.000	25,4	G1253	RG 1000-22-3	.688	17,5	1.312	33,3	.375	9,5
.125	3,2	1.000	25,4	G1255	RG 1000-22-4	.688	17,5	1.313	33,4	.438	11,1
.188	4,8	1.000	25,4	G1256	RG 1000-22-6	.688	17,5	1.313	33,4	.500	12,7
.250	6,4	1.000	25,4	G1257	RG 1000-22-8	.688	17,5	1.313	33,4	.563	14,3
.063	1,6	1.000	25,4	G1258	RG 1000-24-2	.750	19,1	1.250	31,8	.297	7,5
.125	3,2	1.000	25,4	G1259	RG 1000-24-4	.750	19,1	1.188	30,2	.375	9,5
.125	3,2	1.000	25,4	G1260	RG 1000-24-4A	.750	19,1	1.250	31,8	.375	9,5
.188	4,8	1.000	25,4	G1261	RG 1000-24-6	.750	19,1	1.250	31,8	.563	14,3
.250	6,4	1.000	25,4	G1264	RG 1000-28-8	.875	22,2	1.250	31,8	.625	15,9
.063	1,6	1.062	27,0	G1269	RG 1062-24-2	.750	19,1	1.375	34,9	.375	9,5
.188	4,8	1.062	27,0	G1272	RG 1062-24-6	.750	19,1	1.375	34,9	.500	12,7
.250	6,4	1.062	27,0	G1273	RG 1062-24-8	.750	19,1	1.375	34,9	.563	14,3
.375	9,5	1.125	28,6	G1278	RG 1125-24-12	.750	19,1	1.625	41,3	1.125	28,6
.257	6,5	1.125	28,6	G1279	RG 1125-26-8	.804	20,4	1.375	34,9	.506	12,9
.094	2,4	1.125	28,6	G1281	RG 1125-28-3	.875	22,2	1.500	38,1	.344	8,7
.141	3,6	1.187	30,2	G1288	RG 1187-28-5	.875	22,2	1.375	34,9	.406	10,3
.063	1,6	1.250	31,8	G1290	RG 1250-16-2	.500	12,7	1.500	38,1	.250	6,4
.125	3,2	1.250	31,8	G1291	RG 1250-16-4	.500	12,7	1.500	38,1	.313	8,0
.063	1,6	1.250	31,8	G1294	RG 1250-20-2	.625	15,9	1.500	38,1	.250	6,4
.063	1,6	1.250	31,8	G1298	RG 1250-24-2	.750	19,1	1.625	41,3	.250	6,4
.125	3,2	1.250	31,8	G1299	RG 1250-24-4	.750	19,1	1.625	41,3	.313	8,0
.250	6,4	1.250	31,8	G1301	RG 1250-24-8	.750	19,1	1.625	41,3	.438	11,1
.063	1,6	1.250	31,8	G1303	RG 1250-28-2	.875	22,2	1.625	41,3	.438	11,1
.125	3,2	1.250	31,8	G1304	RG 1250-28-4	.875	22,2	1.625	41,3	.500	12,7
.188	4,8	1.250	31,8	G1306	RG 1250-28-6	.875	22,2	1.625	41,3	.563	14,3
.250	6,4	1.250	31,8	G1307	RG 1250-28-8	.875	22,2	1.625	41,3	.625	15,9
.375	9,5	1.250	31,8	G1308	RG 1250-28-12	.875	22,2	1.750	44,5	.750	19,1

Standard color black.