



ALL NEW PRODUCTS!



Heyco® Rubber Grommets

Mounting Diameter: 0.562" to 0.875"

PANEL DIMENSIONS				PART NO.	DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter				Black	A Inside Diameter		B Head Diameter		C Overall Height
in.	mm.	in.	mm.		in.	mm.	in.	mm.	in.	mm.	
.250	6,4	.562	14,3	G1117	RG 562-10-8	.313	8,0	.813	20,7	.500	12,7
.188	4,8	.562	14,3	G1120	RG 562-12-6	.375	9,5	.813	20,7	.375	9,5
.375	9,5	.562	14,3	G1121	RG 562-12-12	.375	9,5	.750	19,1	.750	19,1
.063	1,6	.562	14,3	G1123	RG 562-14-2	.438	11,1	.750	19,1	.250	6,4
.125	3,2	.625	15,9	G1127	RG 625-6-4	.188	4,8	.875	22,2	.250	6,4
.063	1,6	.625	15,9	G1130	RG 625-12-2	.375	9,5	.875	22,2	.313	8,0
.125	3,2	.625	15,9	G1132	RG 625-12-4	.375	9,5	.875	22,2	.375	9,5
.188	4,8	.625	15,9	G1133	RG 625-12-6	.375	9,5	.875	22,2	.438	11,1
.250	6,4	.625	15,9	G1134	RG 625-12-8	.375	9,5	.875	22,2	.500	12,7
.187	4,7	.625	15,9	G1135	RG 625-13-6	.400	10,2	1.100	27,9	.435	11,1
.375	9,5	.625	15,9	G1136	RG 625-13-12	.406	10,3	.813	20,7	.625	15,9
.063	1,6	.625	15,9	G1137	RG 625-16-2	.500	12,7	.813	20,7	.281	7,1
.110	2,8	.630	16,0	G1140	RG 630-16-4	.500	12,7	.810	20,6	.300	7,6
.063	1,6	.687	17,5	G1150	RG 687-14-2	.438	11,8	.938	23,8	.313	8,0
.063	1,6	.687	17,5	G1151	RG 687-14-2A	.438	11,1	.938	23,8	.348	8,8
.125	3,2	.687	17,5	G1152	RG 687-14-4	.438	11,1	.938	23,8	.375	9,5
.188	4,8	.687	17,5	G1153	RG 687-14-6	.438	11,1	.938	23,8	.438	11,1
.250	6,4	.687	17,5	G1154	RG 687-14-8	.438	11,1	.938	23,8	.500	12,7
.063	1,6	.687	17,5	G1155	RG 687-16-2	.500	12,7	.875	22,2	.250	6,4
.188	4,8	.750	19,1	G1172	RG 750-10-6	.313	8,0	1.000	25,4	.438	11,1
.063	1,6	.750	19,1	G1174	RG 750-12-2	.375	9,5	1.000	25,4	.375	9,5
.063	1,6	.750	19,1	G1176	RG 750-16-2	.500	12,7	.875	22,2	.250	6,4
.063	1,6	.750	19,1	G1177	RG 750-16-2A	.500	12,7	1.000	25,4	.250	6,4
.094	2,4	.750	19,1	G1178	RG 750-16-3	.500	12,7	.875	22,2	.344	8,7
.094	2,4	.750	19,1	G1179	RG 750-16-3A	.500	12,7	.969	24,6	.281	7,1
.156	4,0	.750	19,1	G1181	RG 750-16-5	.500	12,7	.938	23,8	.406	10,3
.375	9,5	.750	19,1	G1182	RG 750-16-12	.500	12,7	1.000	25,4	.625	15,9
.125	3,2	.812	20,6	G1188	RG 812-12-4	.375	9,5	1.063	27,0	.375	9,5
.313	8,0	.812	20,6	G1191	RG 812-14-10	.438	11,1	1.063	27,0	.625	15,9
.063	1,6	.812	20,6	G1192	RG 812-16-2	.500	12,7	1.063	27,0	.313	8,0
.125	3,2	.812	20,6	G1193	RG 812-16-4	.500	12,7	1.063	27,0	.375	9,5
.188	4,8	.812	20,6	G1194	RG 812-16-6	.500	12,7	1.063	27,0	.438	11,1
.250	6,4	.812	20,6	G1195	RG 812-16-8	.500	12,7	1.063	27,0	.500	12,7
.063	1,6	.812	20,6	G1197	RG 812-18-2	.563	14,3	1.063	27,0	.313	8,0
.125	3,2	.812	20,6	G1198	RG 812-18-4	.563	14,3	1.062	26,9	.375	9,5
.188	4,8	.812	20,6	G1199	RG 812-18-6	.563	14,3	1.063	27,0	.438	11,1
.250	6,4	.812	20,6	G1200	RG 812-18-8	.563	14,3	1.063	27,0	.500	12,7
.063	1,6	.875	22,2	G1208	RG 875-10-2	.313	8,0	1.375	34,9	.250	6,4
.188	4,8	.875	22,2	G1213	RG 875-18-6	.563	14,3	1.063	27,0	.438	11,1
.375	9,5	.875	22,2	G1214	RG 875-18-12	.563	14,3	1.063	27,0	.625	15,9

Standard color black.

- Used to protect or cover through holes. Help eliminate sharp edges so your wires are protected and add aesthetic value to your application.
- 160 sizes available that will accommodate mounting holes ranging from .250" (6,4 mm) to holes as large as 2.50" (63,5 mm) diameter and panel thicknesses from .063" (1,6 mm) to .375" (9,5 mm).
- Rubber grommets are constructed of SBR with an operating temperature range of -40°F (-40°C) to 221°F (105°C).
- SBR grommets have good water resistant characteristics and are suitable for most moderate chemicals and wet or dry organic acids.

