





## Heyco® Shorty Bushings

PANEL DIMENSIONS				PART NO.		DESCRIPTION	PART DIMENSIONS					
Maximum Thickness		Mounting Hole Diameter		Black	White		A Inside Diameter		B Head Diameter		C Overall Height	
in.	mm.	in.	mm.				in.	mm.	in.	mm.	in.	mm.
.062	1,6	.187	4,7	<b>2800</b>	<b>2801</b>	B 187-125	.125	3,2	.250	6,4	.237	6,0
.062	1,6	.218	5,5	<b>2859</b>	<b>2860</b>	B 218-125	.125	3,2	.281	7,1	.237	6,0
.062	1,6	.281	7,1	<b>2853</b>	<b>2854</b>	B 281-218	.218	5,5	.343	8,7	.237	6,0
.062	1,6	.312	7,9	<b>2810</b>	<b>2811</b>	B 312-250	.250	6,3	.375	9,5	.237	6,0
.062	1,6	.343	8,7	<b>2856</b>	<b>2857</b>	B 343-218	.218	5,5	.406	10,3	.250	6,4
.062	1,6	.375	9,5	<b>2803</b>	<b>2804</b>	B 375-250	.250	6,3	.437	11,1	.250	6,4
.062	1,6	.406	10,3	<b>2806</b>	<b>2807</b>	B 406-281	.281	7,1	.468	11,9	.250	6,4
.062	1,6	.437	11,1	<b>2813</b>	<b>2814</b>	B 437-312	.312	7,9	.500	12,7	.250	6,4
.062	1,6	.468	11,9	<b>2817</b>	<b>2818</b>	B 468-343	.343	8,6	.53	13,5	.250	6,4
.062	1,6	.500	12,7	<b>2820</b>	<b>2821</b>	B 500-375	.375	9,5	.562	14,3	.250	6,4
.062	1,6	.531	13,5	<b>2824</b>	<b>2825</b>	B 531-406	.406	10,3	.593	15,1	.250	6,4
.062	1,6	.593	15,1	<b>2833</b>	<b>2834</b>	B 593-468	.468	11,9	.656	16,7	.250	6,4
.062	1,6	.625	15,9	<b>2827</b>	<b>2828</b>	B 625-500	.500	12,7	.703	17,9	.250	6,4
.062	1,6	.750	19,1	<b>2836</b>	<b>2837</b>	B 750-625	.625	15,9	.828	21,0	.250	6,4
.062	1,6	.781	19,8	<b>2844</b>	<b>2845</b>	B 781-625	.625	15,9	.859	21,8	.250	6,4
.062	1,6	.875	22,2	<b>2850</b>	<b>2851</b>	B 875-750	.750	19,0	.945	24,0	.250	6,4
.062	1,6	1.000	25,4	<b>2847</b>	<b>2848</b>	B 1000-875	.879	22,3	1.06	27,0	.250	6,4
.062	1,6	1.093	27,8	<b>2838</b>	<b>2839</b>	B 1093-969	.969	24,6	1.156	29,4	.255	6,5

Standard color black. Consult Heyco for white and other colors.

Locking fingers in fractional increments up to the maximum panel thickness.

- Available in multiple sizes for use in mounting holes from .187" (4,7 mm) to 1.093" (27,8 mm).
- Insulating feed-thru bushings for limited internal clearance (minimum .125" or 3,2 mm) applications.
- Insulates and isolates electric or telecommunications cables as well as low RPM shafts and push-pull rods.
- Locking fingers hold securely after only fingertip pressure snap-in installation.



Material

6/6 Nylon

Certifications



Recognized under the Component Program of Underwriters' Laboratories, File E15331



Certified by Canadian Standards Association, File LR8919

Flammability Rating

94V-2

Material Temperature Index

257°F (125°C)–Maximum temperature on part not to exceed 221°F (105°C)

*Quick  
Specs*