


MATERIALS:

	CENTER CONTACT	DIELECTRIC	SHELL
1- TYPE 'N' MALE	Gold Plated Brass	Teflon	Silver Plated Brass
2- BNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
3- TNC MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
4- SMA MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
5- TYPE 'N' FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
6- BNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
7- TNC FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
8- SMA FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
9- COUPLING ADAPTER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass
10- DOUBLE BANANA PLUG	Spring: Beryllium copper ASTM B194, alloy 172 cond. Ht. Plug Body: Brass per QQ-B-626, alloy 360, 1/2 hard. Finish: Nickel plated per QQ-N-290, class2, 200/300 microinches Insulation: ABS. Color: Black Center Contact: Gold plated brass Dielectric: Teflon Shell: Silver plated brass		



SCHEMATIC

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ±.005" (.127 mm).
All specifications are to the latest revisions. Specifications are subject to change without notice.
Registered trademarks are the property of their respective companies. Made in USA

6/9/99

SY/EH/LS

C:\Laura Goldberg\FlukeDataSheet\d5748_2_01.doc


Sales: 800-490-2361 Fax: 888-403-3360

Technical Assistance: 800-241-2060

PomonaACCESS 90174 (800) 444-6785 or (425) 446-6010

More drawings available at www.pomonaelectronics.com

Page 1 of 2

11- DOUBLE BINDING POST  <p style="text-align: center;">SCHEMATIC</p>	Body: Brass per QQ-B-626, alloy 360, ½ hard Finish: Nickel plated per QQ-N-290, class 2, 200/300 microinches Insulation: Polycarbonate. Color: one black, one red Insulation, Body: ABS. Color: Black Center Contact: Gold plated phosphor bronz Dielectric: Teflon Shell: Silver plated brass																																																				
	<table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="width: 33%;"></th> <th style="width: 33%;">CENTER CONTACT</th> <th style="width: 33%;">DIELECTRIC</th> <th style="width: 33%;">SHELL</th> </tr> </thead> <tbody> <tr> <td>12- UHF MALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>13- UHF FEMALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>14- MINI UHF MALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>15- MINI UHF FEMALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>16- RCA PHONO MALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>17- RCA PHONO FEMALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>18- TYPE F MALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>19- TYPE F FEMALE</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>20- UNIDAPT SIGNAL SAMPLER</td> <td>Gold Plated Phosphor Bronze</td> <td>Teflon</td> <td>Silver Plated Brass</td> </tr> <tr> <td>21- LABEL, NOT SHOWN</td> <td></td> <td></td> <td></td> </tr> <tr> <td>22- PLASTIC BOX W/ FOAMS</td> <td></td> <td></td> <td></td> </tr> <tr> <td>23- PART CARD, NOT SHOWN</td> <td></td> <td></td> <td></td> </tr> </tbody> </table>		CENTER CONTACT	DIELECTRIC	SHELL	12- UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	13- UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	14- MINI UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	15- MINI UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	16- RCA PHONO MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	17- RCA PHONO FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	18- TYPE F MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	19- TYPE F FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	20- UNIDAPT SIGNAL SAMPLER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass	21- LABEL, NOT SHOWN				22- PLASTIC BOX W/ FOAMS				23- PART CARD, NOT SHOWN			
	CENTER CONTACT	DIELECTRIC	SHELL																																																		
12- UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
13- UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
14- MINI UHF MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
15- MINI UHF FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
16- RCA PHONO MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
17- RCA PHONO FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
18- TYPE F MALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
19- TYPE F FEMALE	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
20- UNIDAPT SIGNAL SAMPLER	Gold Plated Phosphor Bronze	Teflon	Silver Plated Brass																																																		
21- LABEL, NOT SHOWN																																																					
22- PLASTIC BOX W/ FOAMS																																																					
23- PART CARD, NOT SHOWN																																																					

RATINGS:

Operating Temp:

Items 1 through 9 and 12 through 20 : -67° F to +302° F (55° C to +150° C).

Items 10 and 11 : +122° F MAX. (+50° C MAX.)

Nomial Impedance:

Items 1 through 9 and 20: 50 Ohms.

Items 18 through 19: 75 Ohms.

V_{swr} Max.:

Items 1 through 9: 1.2: 1 (DC- 1GHz).

Items 12 through 15: 1.2: (DC- 300MHz).

Frequency Range:

Items 12 through 15: (500MHz MAX.)

Items 16 through 19: (DC to 300MHz).

Item 20: (50MHz to 3GHz).

Weight: 2.40 pounds.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA