

Features/Benefits

- Compact design
- Short stroke to latch
- Wide variety of actuator heights and styles
- Adapted for medium power applications

Typical Applications

- Automotive (air conditioning, lighting)
- Video, remote controls
- Electronic games



Construction

FUNCTION: Momentary, Push-Push
 CONTACT ARRANGEMENT: ²
 PVA1: 2 make contacts (DPST)
 PVA2: 2 change over contacts (DPDT)
 MODE SWITCHING: Non-shorting
 DISTANCE BETWEEN BUTTON CENTERS:
 10, 12,5, 15 (0.394, 0.492, 0.591)
 TERMINALS: PC pins ¹⁾

Mechanical

TOTAL TRAVEL / LATCHING TRAVEL:
 OA: 2,4± 0,2 (0.094 ± 0.008)
 EE: 2,4± 0,2 (0.094 ± 0.008)/ 1,5 (0.059)
 OPERATING FORCE: 1.2 ± .25 (120 grams);
 1.7 ± .25 (170 grams); 3.5 ± .25 (350 grams)

Process

SOLDERABILITY:
 Hand soldering: 350°C for 3 seconds
 Wave or bath soldering: 260°C for 5 seconds
 Cleaning: Use solvents compatible with ABS

Electrical

SWITCHING POWER MAX.: 3 W DC
 SWITCHING VOLTAGE MAX.: 50 V DC
 SWITCHING CURRENT MAX.: 100 mA DC*
 DIELECTRIC STRENGTH (50 Hz / 1 min):
 1000 V between open contacts, PVA2: 750 V
 OPERATING LIFE:
 OA (momentary): ≥ 1 x 10⁶ operations
 EE (push-push): ≥ 1 x 10⁵ operations
 CONTACT RESISTANCE: Initial ≤ 100 mΩ; 50mΩ
 After life:150 mΩ
 INSULATION RESISTANCE: ≥ 10¹⁰ Ω
 BOUNCE TIME: ≤ 3 ms

Environmental


OPERATING TEMPERATURE³⁾: -40°C to 85°C.

- 1) "Snap-in" contacts on request, Version SNA with pins bent inside (standard)
 - 2) Other contact arrangements available by request
 - 3) With button +70°C
- * By 13.8 VDC, the PVA supports a peak current of 500 mA and a continuous current of 20 mA.

NOTE: Specifications listed above are for switches with standard options.
 For information on specific and custom switches, consult Customer Service Center.


How To Order

Our easy build-a-switch concept allows you to mix and match options to create the switch you need. To order, select desired option from each category and place it in the appropriate box.



Please consult factory for ordering code for chassis switch assembly.



Buttons must be ordered separately.
 Shipped in bulk.





PVA Short Stroke Key Switches

SERIES

PVA1 (DPST)





PVA2 (DPDT)





MECHANICAL FUNCTION

OPTION CODE	FUNCTION
OA	Momentary
EE	Push-Push


OA



EE



Cannon




Dimensions shown in: mm (inch)
Dimensions subject to change


PVA Short Stroke Key Switches

TOTAL HEIGHT


H1 17,5 mm




H2 23 mm




H3 20,5 mm



H4 15 mm





H5 13 mm
(momentary only)



TERMINATION

SNA



OPERATING FORCE


NONE PVA1 1.2 N
PVA2 1.7 N

NONE 3.5 N PVA1 & PVA2


BUTTONS

Buttons must be ordered separately. Shipped in bulk.

PE



PV



OPTION CODE	COLOR
RD	Red
GR	Green
BK	Black
WH	White



D

Key Switches