Last Update: 12-28-05 **Ref. #**: MS-100865

Dimensions: mm (In.)



POS. 1	POS. 2
OFF	MOM
OPEN	1-3

SWITCH FUNCTION



PANEL MOUNTING

P.C. MOUNTING

Electrical Specifications:

- Rating: 1A/250VAC, 3A/120VAC or 28 VDC
- Contact Resistance: 20mΩmax. initial @ 2-4VDC 100mA
- Insulation Resistance: 1,000MΩmin.
- Dielectric Strength: 1,000 V RMS@ sea level

Mechanical Specifications:

- Mechanical Life: 60,000 make-and-break cycles.
- Operating Temperature: -30˚C to 85˚C

Note:

- RoHS compliant by exemption

Materials:

- Case: Diallyl phthalate (DAP) (UL94V-0)
- Plunger: Thermoplastic Polyester-black
- Bushing: Brass, nickel plated.
- Housing: Stainless steel
- Contact: Silver or Gold plated.
- Terminal: Brass, Silver plated.
- Terminal Support: Brass, tin plated.

Snap-Acting Pushbutton Switch

107-3025-EVX

Mountain Switch

Available from Mouser Electronics www.mouser.com 1-800-346-6873

Specifications are subject to change without notice. No liability or warranty implied by this information. Environmental compliance based on producer documentation.

Downloaded from Elcodis.com electronic components distributor