

**Last Update:** 8-11-06 **Ref.** #: MS-100493

## Dimensions: mm (In.)







## **Electrical Specifications:**

• Rating: 1A/125VAC

Electrical life: 10,000 operations

Insulation resistance: 1000MΩ (min.) @ 500VDC
Dielectric Strength: 100VAC for 1 minute
Contact resistance: 20mΩ (max.)

11/10/	han	iaal	Cma	aifi	+:	
IVIE	nan	ıcaı	Spe	CITI	cati	ons:

Mechanical life expectancy: 30,000 operations

## **Soldering Specifications:**

• Temperature: 270°C for 3 sec. (Max.)

Mouser Stock No.	Туре	Circuit	Button Color
10PA111	SPST	OFF-(ON)	Red
10PA112	SPST	OFF-(ON)	Black
10PA121	SPST	ON-(OFF)	Red
10PA122	SPST	ON-(OFF)	Black

	1	
Description	Material	Finish
Button	PA	Red, Black, White, Yellow, Blue
Shaft	PA	Black
Knured Nut	C3604BDS	Ep-Cn/Ni
Spring Washer	SWRM-6	Chromium
Hex. Nut	SPCC	Ep-Fe/Ni
Metal	C3602BDS	Ep-Cn/Ni
Body	PF	Black
Terminal	C1100R	Ep-Cn/Ag

Pushbutton Switches 10PA111, 10PA112, 10PA121, 10PA122



Available from Mouser Electronics

www.mouser.com

1-800-346-6873