


*GAX Series Gang  
Jacks Right Angle and*

Features



- Available in 6 and 8 Position Housings
- Available in Both Right Angle and Top Entry Versions
- Ribbed Pin Guides
- Metal Locking Brackets
- UL Recognized File No. E134345
- CSA/NRTL Certified File No. LR78160

Performance Specifications

Materials and Finish

**Housing Material**

Thermoplastic, UL 94V-0 Rated, Gray Color

**Contact Material**

Phosphor Bronze

Electrical Characteristics

**Insulation Resistance**

500 Megohms Min

**Dielectric Withstanding Voltage**

1000V AC RMS for 1 Minute

**Contact Resistance**

20 Milliohms Max

**Current Rating**

1.5 Amps

**MODULAR JACKS AND PLUGS**

**GAX Series**

Documentation & Ordering Information


Kycon Part #

Part Number Builder

Series	Number of Ports	Number of Positions	Plating Option
--------	-----------------	---------------------	----------------

Series  
GAX - Right Angle P.C.B. Mount

Number of Ports, Positions & Contacts

No. of Port	Number of Positions & Contacts				
2	62	64	66	88	-
3	62	64	66	88	-
4	62	64	66	88	88K
5	62	64	66	-	-
6	62	64	66	-	-
7	62	64	66	-	-
8	62	64	66	-	-

K - Key Option

Plating Option  
Standard - Nickel Plating  
50 - 50µ" Gold Plating

Contact Kycon for color and other Options.

[Click here for GAX Part # list](#)