



GDCX-P Series
Perpendicular Through Hole

Features

- Available in 4, 6, and 8 position housings
- Vertical mount
- Through Hole contacts
- CSA certified File No. LR 78160

Performance Specifications

Materials and Finish

Housing Material

PBT thermoplastic UL 94V-0 rated Color: black

Contact Material : Phosphor bronze

Electrical Characteristics

Insulation Resistance :

500 Megohms min.

Dielectric Withstanding Voltage :

1000V rms, 60Hz

Contact Resistance :

20 milliohms max.

Current Rating : 1.5A

Operating Temperature :

-40°C to +85°C

Durability Rating :

500 mating cycles min.

MODULAR JACKS AND PLUGS

GDCX-P Series

Documentation & Ordering Information

Kycon Part #

Part Number Builder

Series	Panel Stop Option	Shield Option	Positions and Contacts	Plating Option		
Series GDCX-P - Perpendicular Through Hole Modular Jacks						
Panel Stop and Shield Options						
Panel Stop & Shield Option	No of Positions and Contacts K - Key Option					
PA With Panel Stops Non-Shielded	44	64	66	88	88K	-
PAS With Panel Stops Shielded	-	-	-	88	88K	-
PN With out Panel Stops Non-Shielded	44	64	66	88	88K	1010 *
PNS With out Panel Stop Shielded	-	-	-	88	88K	-
* Not Available with 50µ" Gold Plating						
Plating Option						
Blank - Standard						
50 - 50µ" Gold Plating						

GDCX-P Series Dimensions

Dimensions in mm

