



5 WATT – COMPACT FOLDING BLADE ADAPTER PSA05F Adapter Meets EISA and ENERGY STAR Requirements



★★★★★
Standby Power



Preliminary

Features

- Folding Blades
- CC & CV control
- EPS 2.0 (Efficiency Level V) *
- 15mm thick with blades folded
- 5 Star Standby power <0.03W

Applications

- MPEG Players
- PDA
- Personal Electronics
- Digital Camera

Safety Approvals (Pending)

- cUL/UL
- SAA
- C-Tick
- CE
- IEEE1725 Approved

Mechanical Characteristics

- Length: 60mm (2.36in)
- Width: 47mm (1.85in)
- Height: 15.0mm (0.59in)
- Weight: 80g (3oz)

Output Specifications

Model	DC Output Voltage	Load		Ripple (1) P-P (max)	Regulation		Efficiency Level
		Min.	Max.		Line	Load	
PSA05F-050Q-H	5V	0A	1.0A	100mV	±5%		Ⓥ

Note: (1) Measured after 10 minutes with by-pass capacitors 0.1uF // 10uF at output connector terminal.

Phihong is not responsible for any error and change. Content is subject to change without notice. Please consult the factory and visit www.phihong.com for the most up-to-date specifications.

INPUT:

AC Input Voltage Rating
100 to 240VAC

AC Input Voltage Range
90 to 264VAC

AC Input Current
0.25A(RMS) max. @ 120VAC
0.125A(RMS) max. @ 240VAC

Leakage Current
0.25mA max. @ 230VAC

Inrush Current (cold)
<30A for 120VAC at max. load
<60A for 240VAC at max. load
(Cold start @ ambient 25°C)

Input Power Saving
0.03W max. @ 230VAC at no load

OUTPUT:
Efficiency
≥ 72.3% average efficiency

Hold-up Time
10mS min. @ 120VAC and max. load

Over-voltage Protection
>120%, Zener Clamp

ENVIRONMENTAL:

Operation 0 to +40°C
Non-operation -25 to +85°C

Humidity
Operation 10 to 90%

Immunity
ESD: EN61000-4-2. Level 3
RS: EN61000-4-3. Level 2
EFT: EN61000-4-4. Level 2
Surge: EN61000-4-5. Level 3
CS: EN61000-4-6. Level 2
Voltage Dips EN61000-4-11
Harmonic: EN61000-3-2

Emissions
FCC Class B
EN55022 Class B

Dielectric Withstand (Hi-pot) Test
Primary to Secondary: 3000VAC

DC Output Connector
USB A
D+ and D- pins shorted together inside the charger

Dimension Diagram Unit: mm