



Dimensions: In.

■ Specifications:

- Type: PC Mount
- Primary Voltage: 115VAC, 60Hz
- Primary Exciting Current: 20mA (max.)
- Secondary Voltage (no load): 14.6CT VAC±0.5V
- Secondary Voltage (full load): 12.6CT VAC±0.5V
- Rated Secondary Current: 0.06 Amp (AC) @ 60Hz
- Voltage Regulation: <16% (VNL-VFL)/(VFL)x100
- Temperature Rise: <45°C
- Breakdown Voltage (HiPOT): 2000VAC @ 50Hz for 1 min
- Coil to Coil Insulation: 200MΩ (min.), 500VDC
- Strain Relief: 5 lbs.
- Channel Frame Material: 0.5mm Thick Iron
- Crossover Insulation: 0.05mm Thick Polyester Tape
- Core Material and Size: HiLite Core H-23, 0.5mm Thick, EI-28
- Inner Insulation: 3 Layers of 0.05mm thick Polyester Tape
- Outer Wrap Insulation: 3 Layers of 0.05mm thick yellow Polyester Tape with 1 piece of Fiber Board
- Bobbin: Nylon, type no. 66 normal, 8mm x 11.2mm
- Impregnation: Varnish
- Lead Wire: AWG23~AWG25
- Lead Length: .591" ± .197"