



Tripp Lite
1111 West 35th Street
Chicago, IL 60609 USA
Telephone: +(773) 869 1234
E-mail: saleshelp@tripplite.com

Model #: PDUB30

Single-Phase Hot-Swap PDU, 30A 120V, 2U Horizontal Rackmount, NEMA 5-15/20R & L5-30R outlets, set of 2 NEMA L5-30P input plugs



Highlights

- 2U rackmount hot-swap PDU enables live replacement of a standard UPS system without shutting down connected server and networking equipment
- Universally compatible with any Tripp Lite or other brand of 100-127V UPS up to 3000VA with a NEMA L5-30P input plug
- Manual transfer switch with lighted status indicators controls PDU output between Utility and UPS power sources
- 2U horizontal rackmount form factor compatible with 2 or 4 post racks
- Pair of attached L5-30P PDU input cables connect to separate Utility and UPS power sources
- 6 Built-in 5-15/20R and 1 L5-30R outlets continuously pass power to critical loads from selectable Utility or UPS input power sources

Description

PDUB30 is universally compatible with any Tripp Lite or other brand of 100-127V UPS rated up to 3000VA with a NEMA L5-30P input plug. Pair of attached L5-30P PDU input cables connect to separate Utility and UPS power sources. 6 5-15/20R and 1 L5-30R outlets support critical networking loads in both Utility and UPS operating modes. 2U rackmount installation in 2 or 4 post racks with support for space saving rear-post mounting in the same rack space as your Tripp Lite Rackmount UPS (select installations, see manual).

Tripp Lite's Hot-swap PDU systems enable live-replacement of standard UPS systems for maintenance with no interruption of connected server or networking loads. Dual input power cables support PDU connection to separate Utility and UPS power sources. Manual transfer switch with lighted status indicators controls the source of power to connected equipment between Utility and UPS. Set the switch to UPS during normal operation and connected equipment will receive full-time conditioned power from the UPS. Set the switch to Utility to momentarily power connected equipment from the Utility line cord and bypass the UPS while the UPS system is removed and replaced with a fresh one. Once the new UPS is up and running with all data and electrical connections restored, set the switch back to the UPS setting to once again provide fully-conditioned UPS power to connected equipment.

Applications

Hot-swap PDUs are ideal to install along with standard UPS systems to ensure that connected networking equipment will see no power interruption as the UPS is serviced, replaced or upgraded

Package Includes

- Hot-swap PDU System
- 2U mounting brackets
- User manual with warranty information

Features

- Tripp Lite Hot-swap PDU systems support live-replacement of standard UPS systems for maintenance with no interruption of connected server or networking loads
- PDUV30 is universally compatible with any Tripp Lite or other brand of 100-127V UPS rated up to 3000VA or 2880 watts with a NEMA L5-30P input cable
- 2U horizontal rackmount form factor compatible with 2 or 4 post racks
- Supports space saving rear-post mounting in the same rack space as many Tripp Lite Rackmount UPS systems (select installations, see manual)
- Pair of attached L5-30P PDU input cables connect to separate Utility and UPS power sources
- 6 5-15/20R and 1 L5-30R outlets support critical networking loads in both Utility and UPS operating modes
- One additional L5-30R pass-through outlet supports UPS input power cord
- Dual input power cables support PDU connection to separate Utility and UPS power sources
- Manual transfer switch with lighted status indicators controls the source of power to connected equipment between Utility and UPS
- Set the switch to UPS during normal operation and connected equipment will receive full-time conditioned power from the UPS
- Set the switch to Utility to bypass the UPS and provide connected equipment with unfiltered power directly from the Utility line cord while the UPS system is removed and replaced with a fresh one
- Once the new UPS is up and running with all connections restored, set the switch back to the UPS setting to once again provide fully-conditioned UPS power to connected equipment

Specifications

OVERVIEW	
Model Type	Hot-Swap
PDU Type	Hot-Swap
OUTPUT	
Output Watt Capacity (watts)	2880
Frequency compatibility	50 / 60 Hz
Output nominal voltage	100V, 120V, 127V
Outlet quantity / type	6 NEMA 5-15/20R and 1 L5-30R outlets support critical connected loads; 1 designated pass-through L5-30R outlet supports UPS L5-30P input plug
INPUT	
PDU Input Voltage	100; 120; 127
Recommended Electrical Service	Compatible with 100-127V UPS systems rated to 3000VA that use a L5-30P input plug
Maximum Input Amps (A)	24
Input connection type	UTILITY & UPS input line cords both fitted with NEMA L5-30P input plug
Plug Type	Two NEMA L5-30P (30A 120V)
PDU Plug Type	NEMA L5-30P
Input cord length details	Utility input cable (10 ft / 3m) / UPS input cable (6 ft / 1.8m)
Voltage compatibility (VAC)	100-127
Phase	Single-Phase
LEDS ALARMS & SWITCHES	
Switches	Manual 2 position transfer switch offers fast switching between UPS and Utility operating modes in less than 6 milliseconds
Front panel LEDs	Lighted indicators confirm UPS and Utility switch position and operating mode

PHYSICAL	
Shipping weight (lbs)	11
Shipping weight (kg)	5
Unit Dimensions (HWD/in)	3.42 x 17.32 x 3.03
Unit Dimensions (HWD/cm)	8.7 x 44 x 7.7
Shipping Dimensions (HWD/in)	9.25 x 20.23 x 6.1
Shipping Dimensions (HWD/cm)	23.5 x 51.4 x 15.5
Unit weight (lbs)	7.7
Unit weight (kg)	3.5
Material of construction	Steel
Style	Rackmount
Form factors supported	2U rackmount in 2 or 4 post racks
PDU Form Factor	Horizontal (1U, 2U, etc)
ENVIRONMENTAL	
Relative Humidity	0-95% non condensing
CERTIFICATIONS	
Certifications	Tested to UL60950 (USA), CSA (Canada)
WARRANTY	
Product Warranty Period (U.S., Canada & Puerto Rico)	2-year limited warranty

Related Items

Optional Products

Product Type	Related Model	Description	Qty.
Power Cables	P012-006	6-ft. Notebook Power cord (NEMA 1-15P to IEC-320-C7)	-
Power Cables	P007-002	2-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P007-006	6-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P007-010	10-ft. Heavy-Duty 14AWG Power cord (IEC-320-C13 to NEMA 5-15P)	-
Power Cables	P010-012	12-ft. 18AWG Power cord (NEMA 5-15P to IEC-320-C13)	-
Power Cables	P022-001	1-ft. 18AWG Power Extension cord (NEMA 5-15R to NEMA 5-15P)	-
Power Cables	P023-001	1-ft. 14AWG Power Adapter cord (NEMA L5-15R to NEMA 5-15P)	-
Power Cables	P034-010	10-ft. 14AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-15P)	-

Power Cables	P044-061	6-inch 12AWG Heavy Duty Power Adapter cord (NEMA-L5-20R to NEMA-5-20P)	-
Power Cables	P049-010	10-ft. 12AWG Heavy Duty Power cord (IEC-320-C19 to NEMA 5-20P)	-

More information, including related products, owner's manuals, and additional technical specifications, can be found online at www.tripplite.com/en/products/model.cfm?txtModelID=4467.

Copyright © 2011 Tripp Lite. All rights reserved. All trademarks are the sole property of their respective owners. Tripp Lite has a policy of continuous improvement. Specifications are subject to change without notice. Photos may differ slightly from final products.