



Test Equipment Accessories



Amp-Clamp Adapters

Amp-Clamp current probes, used with analog VOMS provide accurate measurements of high AC current found in power systems and related control circuitry. The Amp-Clamp jaws are closed over a conductor in the circuit and the current load is indicated on the connected meter. The 150-2 has six ranges (up to 300 ACA) and is available with banana and reverse banana plugs.



Model No. 150-2

Specifications

AC AMP-CLAMP ADAPTER

Model	150-2
Ranges	5A, 10A, 50A, 100A, 250A (on 2.5 VAC Meter Range), 6A, 12A, 30A, 60A, 120A, 300A (on 3 VAC Meter Range)
Accuracy	± 3% Full Scale

PHYSICAL


Dimensions: 7.8" x 3" x 1.1"

Weight: 12 oz.

Max. Cable Dimension: 1.125" diameter

Max. Bus Bar Dimensions: 2.38" x 0.38"

Battery Adapter Kit



Model No. 45002

AMP-CLAMP	Catalog No.	BATTERY ADAPTER KIT	Catalog No.
150-2 AC Clamp, VOM Banana Plug	00541	260-5 Battery Upgrade	45002
150-2 AC Clamp, VOM Reverse Plug	00545		
Cable, replacement, reverse banana (used with 00545)	00529		
Cable, replacement, banana (used with 00541)	00533		