



# 260-8Xi<sup>®</sup> & 260-8XPi<sup>®</sup> Analog VOM

260-8Xi has all of the circuit protection features and advantages for which the 260 Series is famous...

And even more features than its predecessors. The yellow case color for enhanced visibility and user safety awareness is the trademark of the 260-8Xi. The durable ABS plastic case also provides high-impact resistance and increased drop protection in the toughest environments.

- Instant Trend Information for Quick Positive "Yes/No" Checks
- Zero RFI Emission
- UL Listed
- Audible Continuity Check
- Resettable Overload Circuit Protection Relay
- 1.5 V and 9 V Batteries and Probe Test Leads With Alligator Clips
- Mirrored Scale for Parallax Reduction



## Specifications

### DC VOLTAGE

Ranges	Accuracy	Sensitivity
250mV, 2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	2% of full scale	20k $\Omega$ per volt

### AC VOLTAGE

Ranges	Accuracy	Sensitivity
2.5V, 10V, 25V, 50V, 250V, 500V, 1000V	3% of full scale	5k $\Omega$ per volt

### DECIBEL

5 Ranges: -20 to +50dB

Reference: 0dB= 1mW into 600 $\Omega$

### AC CURRENT

Up to 250 AC amperes with AC Amp-Clamp Adapter Accessory 00541.

### DC CURRENT

Ranges	Accuracy	Voltage Drop: (Nominal)
50 $\mu$ A, 1mA, 10mA, 100mA, 500 mA, 10A	1.5% full scale 50 $\mu$ A 2.0% of full scale, all others	250mV on 50 $\mu$ A/1mA; 255mV on 10mA/10A; 300mV on 100mA; 500mV on 500mA

## Ordering Information

VOM	Catalog No.	ACCESSORIES	Catalog No.	ACCESSORIES	Catalog No.
260-8Xi, Yellow	12395	Probe Leads w/Screw-on Alligator Clip	00125	Case, Yellow Padded Polyester	00832
260-8XPi, Protected, Yellow	12396	Probe Set, Replaceable Tip, Banana Lead Set, Alligator, Banana Clip Set, Alligator, Screw-On	07538 07500 00425	Case, Black Padded Polyester Case, Hard Leatherette Front Load Case, Molded Plastic	00834 00805 45028
		150-2 Amp Clamp Adapter, AC	00541		

Additional accessories are on pages 21-23.

## Specifications (Continued)

### RESISTANCE

Ranges	Accuracy	Maximum Indication
Rx1 Rx100 Rx10k	2.5° of arc on Rx1 2.0° of arc on all others	0-2k $\Omega$ 0-200k $\Omega$ 0-20m $\Omega$

**BATTERIES:** 1.5 V AA, 9V (NEDA No. 13F, 1604A)

**FUSE:** F1 1A, 250V, type 3AG, quick acting Littelfuse<sup>®</sup> Type 312001; F2 2A, 600V Littelfuse<sup>®</sup> Type BLS or 2A 600V, Bussman<sup>®</sup> Type BBS.

**SIZE:** 5 1/4" x 7" x 3 1/8" (13.34 x 17.78 x 7.94 cm)

**WEIGHT:** 2 1/4 lbs. (1.02 Kg)

**RATED CIRCUIT-TO-GROUND VOLTAGE:** 1000V AC/DC Max

Specifications subject to change without notice.