

Models 2405A, 2407A, 2408

Mini-Pro® Multimeters

Data Sheet





2405A

The Model 2408
features a unique noncontact voltage indicator.
Light and sound denote the
presence of AC voltage from
70V to 480VAC @50 - 60Hz.
This eliminates the need for
an extra tool to carry in
your tool box.



The Mini-Pro® multimeters are a professional quality multimeter at low cost. Three new meters with a price point that will put them in every toolbox and field service kit. The unique design fits easily in the palm of your hand and CE approval ensures safe operation. Manual and autoranging models offer the basic functionality needed to do 90% of most required testing.

These meters are the best value for any hobbies. No home should be without one!

Common Features:

- DC/ACvoltage to 600V
- ■DC current to I0A
- Resistance to 20M Ω (model 2407A 31M Ω)
- Diode test
- **■** Low battery indicator
- **CE** approved

Features		r	nodels
	2405A	2407A	2408
Basic Functions			
Display Counts	2000	3200	2000
Basic DC Accuracy	2.0%	1.2%	1.2%
Ranging	Manual	Auto	Manual
Current	10A DC	10A AC/DC	10A AC/DC
1.5V & 9V Battery Test	√		
Auto Zeroing	√		√
Bar Graph		√	
Auto Power Off		√	
Continuity		√	√
Data Hold		√	√
Max. Hold			√
Non-contact Voltage Indicator			√

B&K Precision Corporation

22820 Savi Ranch Parkway, Yorba Linda, CA 92887 Tel: 714-921-9095, Fax: 714-921-6422 www.bkprecision.com



Model HV-44A

40KV High Voltage Probe Meter

The HV-44A is a self-contained instrument that measures high DC voltages up to +40KV. This probe is typically used to measure high voltages in TV sets, power supplies, laboratories and for general high voltage commercial applications.

Specifications model		
	HV-44A	
Voltage range	0 to +40KV DC	
Input Impedance	600MΩ, nominal	
Accuracy	±3% of full scale.	
Calibration	Internal, factory calibrated at 25KV	
Size	16.5 x 2.125 x 2" with a 34" long ground cord	
	(419 x 54 x 50mm with a 86.4cm long ground cord)	
Probe Tips	Two interchangeable tips; one round needle type,	
	one special flat spring type for easy access to CRT anode.	
	One Year Warranty	

Specifications subject to change without notice