


Model 3789 BNC Male To Minigrabber® Test Clip Breakout



FEATURES:

- Minigrabber® test clip hooks attach to terminal sizes up to .060" diameter
- Converts BNC (Female) jacks to Minigrabber test clips for test versatility
- BNC connector and Minigrabber test clip caps are molded directly onto the wire for pull strength durability and dust and moisture resistance
- Grabber hook and BNC center contact are Gold-plated Beryllium Copper for optimum strength, excellent corrosion resistance and low contact resistance to ensure test signal integrity
- Schematic: Black Minigrabber test clip to BNC shell, red Minigrabber test clip to BNC center contact

MATERIALS:

BNC: Nickel plated brass

Center Contact: Gold-plated brass

Insulation: polypropylene molded to BNC and wire

Wire: 20 AWG, PVC

Marking: "POMONA 3789"

Minigrabber® test clip:

Contact: Gold-plated Beryllium Copper,

Insulation: Glass filled nylon, color: red and black Marking: "Pomona Electronics", "Minigrabber®"

RATINGS:

Operating Temperature: +55°C (+131°F) Max.

Operating Voltage: Hand-held testing: 30VAC/60VDC Max.

Hands free testing in controlled voltage environments: 300VRMS Max.

ORDERING INFORMATION: Model 3789

All dimensions are in inches.

All specifications are to the latest revisions. Specifications are subject to change without notice. Registered trademarks are the property of their respective companies. Made in USA

5/30/02 SY/EH/LS

Last saved by PN S:\Engineering\Release\DataSheets\FlukeDataSheet\d3789 1 02.doc

Technical Assistance: 800-241-2060

Sales: 800-490-2361 Fax: 888-403-3360

Pomona ACCESS 90334 (800) 444-6785 or (425) 446-6010 More drawings available at www.pomonaelectronics.com

Page 1 of 1