all 0.070" pads have 0.050" plated through holes on 0.100" grid lines between adapters grooved for easy snap-apart by hand board thickness 0.031" print 1:1 to fit check components front side

moo.	peldynsys	PER STATE OF THE PER ST	INC		DYNAMIC	NITTER	© 2002		# 213 <sub>+</sub>
1/206 0 0 0 0 0 0 0 0	97.10S	9710S	97.10S	\$210S	97.05 92.05	7/20S	97.10S	PZLOS	7/20S
9210S	97.10S	9/20S 0	\$01.70 \$01.70	9Z10S	97.08 97.108	97.10S	97.10S	97.10S	97.00S
9806	98206 9 11 0 9 12 0 9	0 0000 0 0 0 0 0	00000 0 0 1 0 0 00000	0 0000 0 0 000000	9825 0 0 1 0 0 0 0 0	0 0000 0 0 0000 0	98205 0 0 1 1 0 0 0 0 0 0	9805 0 0 1 0 0 0 0 0	9905 0 0 1 0 0 0 0 0
	0 0000 0 0 1 0 0 00000	0 0000 0 0 1 0 0 00000	0 2020 0 1 0 0 0 20200	0 2020 0 0 1 0 0 0 0 0 0	0 00000 0 0 1 0 0 0 0 0	0 2020 0 0 1 0 0 002000	98235 0 0 1 1 0 0 1 1 0	9000 0 0 1 0 0 00000	0 2020 0 1 0 0 0 20200
SZ-OI	201-100 201-120	CSZ-01 [57	251 TO 251	100-202 2011/2	201-202 201-122	27110S	297-01 271105	27 LLOS	571105
	SOTING SCOTING	SSET SECTION S	SSTATE SOLUTION STATE ST	SSET OF THE PROPERTY OF THE PR	SOT SECTOR	SZEZE SZ SZ SZ SZ SZ SZ SZ SZ SZ SZ SZ SZ SZ	SS COS	SCTSS	SS S S S S S S S S S S S S S S S S S S
188	\$5738 \$5596	¥8578 4586 €	\$5778 \$588 €	¥8578 48 86 €	SC734 SC986	85738 8688 €	250 S S S S S S S S S S S S S S S S S S S	¥5575 45.85 15.05	\$0734 \$088

