



Tape X-7001

Copper-Coated Polyester Cloth Double-Coated with Conductive Adhesive

Data Sheet

Product Description

3M™ Tape X-7001 consists of a flexible copper-plated polyester fabric backing that is coated on both sides with a unique electrically conductive pressure-sensitive acrylic adhesive.

- Copper-plated polyester woven fabric backing
- Conductive acrylic adhesive on both sides
- Supplied with removable liner on both sides for easy handling and die-cutting

Please consult with sales representatives about custom width and length. Standard length is 10 m.

Applications

3M Tape X-7001 is typically used to bond two surfaces together, both electrically and physically. An example would be adhering a conductive gasket to another conductive gasket to a conductive surface as part of the EMI shielding solution for an electronic enclosure. The unique metallized fabric backing offers the additional benefits of excellent flexibility and conformability. The fabric backing also minimizes the possibility of finger lacerations.

Conductivity

Since 3M Tape X-7001 double-sided metallized fabric conductive tape would typically be used as an electrical path between two surfaces, its most important feature is its conductivity. Conductive particles in the acrylic adhesive provide a multitude of electrical paths between the application substrate and the surface of the aluminum foil on each side. The resistance of the conductive path through the adhesive (measured over a 25 x 25 mm area) typically measures 15-20 milliohms.

Properties	Typical Values
Total thickness (backing plus adhesive) ¹	0.11 mm
Adhesion to steel ¹	6.4 N/cm
Electrical resistance through adhesive ²	0.015 Ω (over a 25 x 25 mm area)

Footnote: 1. Test method ASTM-D-1000
2. S/3M Test method 1

3M is a trademark of 3M Company.

Important Notice

Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use.

Warranty; Limited Remedy; Limited Liability. This product will be free from defects in material and manufacture as of the date of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any loss or damage arising from this 3M product, whether direct, indirect, special, incidental or consequential regardless of the legal theory asserted.**



Electrical Markets Division

6801 River Place Blvd.

Austin, TX 78726-9000

www.3M.com/electrical/oem

Litho in USA

© 3M 2004 78-8126-6595-4-A