



FEATURES:

- Wire firmly held in place with internal set screw.

MATERIALS:

Upper Conn.: Miniature Banana Jack

Material: Brass per QQ-B-626, Alloy 360, 1/2 Hard.

Finish: Gold plate per MIL-G-45204, Type II, Class 00 over electroless nickel per MIL-C-26074, Class 1 (.0002/.0003).

Insulation: ABS molded to Banana Jack and Banana Plug Body.

Color: See Ordering Information

Marking: "POMONA ELECTRONICS, 2944".

Lower Conn.: Miniature Banana Plug

Material: Body – Same as above

Spring – Beryllium Copper per QQ-C-533, Berylco 25, Cond. H.T.

Finish: Same as above.

Cross Hole: 2.08 (.082) dia. with #3-56 slotted set screw to secure lead wires.

RATINGS:

Operating Temperature: +50°C. (+122°F.) Max.

Operating Voltage: 2500 VDC

Current: 5 Amperes Cont.

ORDERING INFORMATION: Model 2944-*

*=Color, -0 Black, -2 Red

Ordering Example: 2944-2 Color is Red.

All dimensions are in inches. Tolerances (except noted): .xx = ±.02" (.51 mm), .xxx = ± .005" (.127 mm).

All specifications are to the latest revisions. Specifications are subject to change without notice.

Registered trademarks are the property of their respective companies. Made in USA