


## FL CAT5 PATCH 2,0

Order No.: 2832289

<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2832289>

Patch cable, CAT5, assembled, 2.0 m

**Commercial data**

GTIN (EAN)	
sales group	K009
Pack	10 pcs.
Customs tariff	85444210
Catalog page information	Page 203 (AX-2009)

**Product notes**WEEE/RoHS-compliant since:  
11/07/2006

<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

**Technical data****External sheath**

Outer sheath, material	LSFROH
External diameter	5.5 mm

**Single wire**

Individual wires per module	8
Single wire, material	Cu litz wire

---

Single wire, cross section	0.14 mm <sup>2</sup>
----------------------------	----------------------

**Mechanical properties**

Smallest bending radius, fixed installation	30 mm
Ambient temperature (operation)	-10 °C ... 60 °C

**General data**

Nominal voltage U <sub>N</sub>	150 V <sub>rms</sub>
--------------------------------	----------------------

**Accessories**

Item	Designation	Description
<b>General</b>		
2891194	FL PATCH CCODE BK	Color marking for patch cable, black
2891495	FL PATCH CCODE BN	Color marking for patch cable, brown
2891291	FL PATCH CCODE BU	Color marking for patch cable, blue
2891796	FL PATCH CCODE GN	Color marking for patch cable, green
2891699	FL PATCH CCODE GY	Color marking for patch cable, gray
2891893	FL PATCH CCODE RD	Color marking for patch cable, red
2891990	FL PATCH CCODE VT	Color marking for patch cable, purple
2891592	FL PATCH CCODE YE	Color marking for patch cable, yellow
2891424	FL PATCH GUARD	Lockable security element
2891246	FL PATCH SAFE CLIP	Security element for FL patch cable

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;