

Fabric

2:1 Fabric Heatshrink Tubing

Shrinks to 1/2 it's original diameter. Fabric heatshrink tubing, a unique mixture of Polyolefin and Polyester yarns, is the ideal way to form the only shrinkable fabric of its kind. The woven construction makes this product extremely flexible and resistant to trapping water, heat and humidity. Provides outstanding abrasion, chafing and cutting protection, even at high temperatures.

Shrinkflex fabric tubing is designed primarily to provide mechanical abrasion protection for components such as rubber hoses, plastic pipes, and harness wiring bundles. Also suitable for other applications, such as noise and rattle suppression.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/2"	H2F0.48BK	12mm	6mm	100'	25'	Black (BK)	1.15
3/4"	H2F0.79BK	20mm	10mm	100'	25'	Black (BK)	1.61
1"	H2F0.98BK	25mm	12.5mm	100'	25'	Black (BK)	1.71
1 3/16"	H2F1.18BK	30mm	15mm	100'	25'	Black (BK)	2.13
1 3/8"	H2F1.38BK	35mm	17.5mm	100'	25'	Black (BK)	2.35
1 1/2"	H2F1.58BK	40mm	20mm	100'	25'	Black (BK)	2.66
2"	H2F1.97BK	50mm	25mm	100'	25'	Black (BK)	3.44
2 3/8"	H2F2.36BK	60mm	30mm	100'	25'	Black (BK)	4.11
2 3/4"	H2F2.75BK	70mm	35mm	100'	25'	Black (BK)	4.69
3 1/8"	H2F3.15BK	80mm	40mm	100'	25'	Black (BK)	5.29

- **Shrink Temp. 176°F**
- **Highly Flexible**
- **Resists Common Automotive Chemicals**
- **Easily Installs Over Connectors & Splices**
- **Halogen Free**



Diesel Resistant

2:1 Diesel Resistant Heatshrink Tubing

Diesel resistant heatshrink tubing is the ideal way to create a tight, professional finish on any wire, hose or cable management project. Once shrunk, the tubing will hold its reduced state even in elevated temperatures. H2D is resistant to aviation and diesel fuels, hydraulic fluids and lubrication oils. It will protect wires, solder joints, terminals, connections and components from most industrial fuels and abrasion.

Nominal Size	Part #	Unshrunk Diameter	Shrunk Diameter	Standard Spool Put-Ups		Available Colors	Lbs/100'
				Bulk Spool	Shop Spool		
1/8"	H2D0.13BK	3.2mm	1.6mm	500'	25'	Black (BK)	0.70
3/16"	H2D0.19BK	4.8mm	2.4mm	250'	25'	Black (BK)	1.00
1/4"	H2D0.25BK	6.4mm	3.2mm	250'	25'	Black (BK)	1.20
3/8"	H2D0.38BK	9.6mm	4.8mm	200'	25'	Black (BK)	1.75
1/2"	H2D0.50BK	12.8mm	6.4mm	100'	25'	Black (BK)	2.75
3/4"	H2D0.75BK	19.3mm	9.5mm	100'	25'	Black (BK)	4.75
1"	H2D1.00BK	25.4mm	12.7mm	100'	25'	Black (BK)	8.80
1 1/4"	H2D1.25BK	31.8mm	15.9mm	100'	25'	Black (BK)	
1 1/2"	H2D1.50BK	38.2mm	19.1mm	100'	25'	Black (BK)	

- **Shrink Temp. 302°F**
- **Heavy Wall, Flexible Elastomer Polyolefin Tubing**
- **High Resistance to Aviation Fuels, Diesel Fuels and Oils**

800 323-5140
www.techflex.com

*Contact your Account Representative for heatshrink cutting & printing services.