



## **TECHNICAL DATA SHEET**

www.tycoident.com

Document number: TTDS-080

Issue: 2

Date: July 2006

1910

Thermal Transfer Ribbons

MATERIAL Resin based thermal transfer ribbon for use with Tyco Electronics HX,

**DESCRIPTION:** HLX and HXTM zero halogen markers.

For all T312M printer users the 1966-RIBBON is now the

recommended ribbon (see data sheet TTDS-099)

**APPLICABLE** T408M: HLX Cable markers, HXTM-FB Terminal marker

PRINTERS/ PRODUCTS: HSPRINT4: HLX, HXTM-FB, HX marker sleeves

SHELF LIFE: 2 years when stored between -5°c (23F) and 40°c (104F)

COLOR: Black.

**DIMENSIONS:** 210m x 110mm (689' x 4.33")

WINDING DIRECTION: 19100000-RIB-BK-HI-DUR Ink side in 1910-RIBBON-4T300 Ink side out

ORDERING 19100000-RIB-BK-HI-DUR for HSPRINT4series printers

**INFORMATION:** 1910-RIBBON-4T300 for T400 series printer

**PRINT PERFORMANCE**See Individual product technical data sheets

Page 1 of 1

**Business locations:** 

N America: + 1 650 361 3860 (West Coast)

**Germany:** + 49 (0) 6074 89080

UK: + 44 (0) 1495 244000 (Labels)

Japan: + 81 (0) 44 900 5102

N America: + 1 401 751 6505 (East Coast)

France: + 33 (0) 476 099696

WK: + 44 (0) 1793 528171 (Other products)

Singapore: + 65 (0) 4866 151

All the above information, including illustrations, is believed to be reliable. Users, however, should independently evaluate the suitability of each product for their application. Tyco Electronics makes no warranties as to the accuracy or completeness of the information and disclaims any liability regarding its use. Tyco Electronics only obligations are those in the Standard Terms and Conditions of Sale for this product and in no case will Tyco Electronics be liable for any incidental, indirect or consequential damages arising from the sale, resale, use or misuse of the product. Tyco Electronics Specifications are subject to change without notice. In addition Tyco Electronics reserves the right to make changes in materials or processing, without notification to the Buyer, which do not affect compliance with any applicable specification.