

REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
G	REVISED AND RENAMED PER ECN# T-17723	93 JAN 14	Z. TEMAN
H	REVISED PER ECN# T-18023	93 FEB 1	Z. TEMAN
J	REVISED PER ECN# T-21046	96 OCT 8	Z. TEMAN

NOTES:

△ 1 DK-621-X413 NOT INCLUDED.

KIT △	PCN NO.	CONNECTOR	CONTACT	USAF NO. △
DK-621-0411	228389	PLUG	----	N/A
DK-621-0411-P	902973	PLUG	PIN	8340709-00-01
DK-621-0411-UP	980023	PLUG	PIN	N/A
DK-621-0411-S	191045	PLUG	SOCKET	8340709-00-02
DK-621-0411-US	580047	PLUG	SOCKET	N/A
DK-621-0412	149527	JACK	----	N/A
DK-621-0412-P	118345	JACK	PIN	8340711-00-01
DK-621-0412-UP	734977	JACK	PIN	N/A
DK-621-0412-S	503123	JACK	SOCKET	8340711-00-02
DK-621-0412-US	682615	JACK	SOCKET	N/A
DK-621-0414	341103	JACK	----	N/A
DK-621-0414-P	046369	JACK	PIN	N/A
DK-621-0414-S	875101	JACK	SOCKET	N/A

NOT AVAILABLE FOR NEW ORDERS ORDER EQUIVALENT DK-621-041X(-XX) CONNECTOR			
DK-621-1411	459727	PLUG	----
DK-621-1411-P	856385	PLUG	PIN
DK-621-1411-UP	054769	PLUG	PIN
DK-621-1411-S	824175	PLUG	SOCKET
DK-621-1411-US	087739	PLUG	SOCKET
DK-621-1412	171793	JACK	----
DK-621-1412-P	839897	JACK	PIN
DK-621-1412-UP	650513	JACK	PIN
DK-621-1412-S	051167	JACK	SOCKET
DK-621-1412-US	544577	JACK	SOCKET

SPECIFICATION CONTROL DRAWING


UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES.
METRIC DIMENSIONS ARE
IN BRACKETS.

DECIMALS
.XXX ± [] mm
.XX ± [] mm

ANGLES
.X ± []

WEIGHT
[] lbs. [] g

DRAWN	J.B.K.	92 MAR 3
CHECKED		
APPROVED		
APPROVED	Z.TEMAN	92 MAR 3
CAD NAME	004990-1	




	Tyco Electronics Corporation 300 Constitution Drive Menlo Park, CA. 94025 U.S.A.	
	TITLE KITS FOR D-621 THREADED 400 SERIES TRIAXIAL CONNECTORS (FOR TWINAXIAL CABLES)	

SIZE	CODE IDENT. NO.	DWG. NO.	REV
A	06090	DK-621-X411/X414[-XX]	J

NOTES: (CONTINUED)

△ USAF No.: PLUG - 8340709-00-0X } PRINTED ON STRAIN RELIEF OF
 JACK - 8340711-00-0X } DK-621-04YY SERIES.

3. D-600-0030 BRAID TERMINATOR REPLACES D-600-0055 AND D-600-0056.



REQUIREMENTS:

1.0 REFER TO THE FOLLOWING RAYCHEM SPECIFICATION CONTROL DRAWINGS (SCD) FOR INDIVIDUAL COMPONENT DETAILS:

D-621-0411	CONNECTOR, TRIAXIAL, SUBMINIATURE	
D-621-0412		
D-621-0414		
D-602-0126	CONTACT, PIN	NOT SHOWN
D-602-0127	CONTACT, SOCKET	NOT SHOWN
D-600-0030	BRAID TERMINATOR	NOT USED WITH DK-621-0414(-X)
D-600-0019	STRAIN RELIEF	

2.0 CONNECTORS ARE QUALIFIED TO RAYCHEM SPECIFICATION D-6025.

3.0 TERMINATION PROCEDURE: RAYCHEM ES 61162