


# VS-15-ST-DSUB-2P-5S

Order No.: 1688227




<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1688227>

D-SUB contact insert, shell size 2, with five signal contacts with solder cup, straight, accommodation for two combined contacts, contact type pin, fixing with a 3 mm hole, for panel mounting frame and sleeve housing VS-15-...

Commercial data	
GTIN (EAN)	 4 017918 179625
sales group	D501
Pack	10 pcs.
Customs tariff	85366990
Catalog page information	Page 323 (PC-2009)

**Product notes**

WEEE/RoHS-compliant since:  
04/14/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Mechanical characteristics	
Number of positions	7
Insertion/withdrawal cycles	≥ 200
Type of connection	Solder cup
Conductor cross-section	0.5 mm <sup>2</sup>
Connection cross-section AWG	20

Insertion force per signal contact	≤ 3.40 N
Extraction force per signal contact	≥ 0.2 N
Ambient temperature (operation)	-55 °C ... 125 °C

**Material data**

Inflammability class acc. to UL 94	V0
Housing material	Steel, yellow chromated
Contact carrier material	PBTP
Contact material	Copper alloy
Contact surface material	Gold over nickel

**Electrical characteristics**

Rated voltage (III/3)	250 V
Rated surge voltage	1 kV
Rated current	5 A
Contact resistance per contact pair	≤ 2.7 mΩ
Insulation resistance	≥ 5 GΩ

**Accessories**

Item	Designation	Description
<b>Contacts</b>		
1655548	VS-ST-KX-50-RG174	Coaxial contact, for D-SUB combination inserts, solder cup, pin, straight, for cable RG 174, gold-plated
1655506	VS-ST-KX-50-RG178	Coaxial contact, for D-SUB combination inserts, solder cup, pin, straight, for cable RG -178, gold-plated
1655580	VS-ST-KX-50-RG58	Coaxial contact, for D-SUB combination inserts, solder cup, pin, straight, for cable RG 58, gold-plated
1655629	VS-ST-KX-75-RG179/187	Coaxial contact, for D-SUB combination inserts, solder cup, pin, straight, for cable RG 179/187, gold-plated
1655483	VS-ST-SC-2,6	Power contact, for D-SUB combination inserts, screw connection, pin, straight, rated current 20 A, gold-plated


**General**

1688243	VS-ST-LK-3,6/22,4/2,6	Power contacts, for D-SUB combination inserts, pin, solder cup, straight, rated current 20 A, gold-plated
1688269	VS-ST-LK-3,6/22,4/4,6	Power contacts, for D-SUB combination inserts, pin, solder cup, straight, rated current 40 A, gold-plated

## Diagrams/Drawings

### Dimensioned drawing

D-SUB contact insert



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;