


STRIPPING DIMENSION



Directive 2002/95/EC RoHS compliant

3	1	RETAINING RING	COPPER ALLOY	NICKEL PLATED
2	1	REAR SIDE	COPPER ALLOY	GOLD FLASH over NICKEL
1	1	FRONT SIDE	COPPER ALLOY	min. 30µin HARD GOLD over min. 50µin NICKEL
pos	qty	description	material	plating

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND		partlist		tolerance	scale: 5:1 material: SEE PARTLIST
		ISO 2768-m		dim. in mm	
drawn	03.01.11	name	Henneboel	<b>HIGH POWER CONTACT MALE</b> SOLDER CUP 30A FOR AWG 10-12; d=3,5mm D-SUB COMBINATION	
appd.	03.01.11	name	Koch		
norm				dwg no:	DIN-A3 sh: 1
d-old				13K1A3531	
a	Origin			part no:	131C10139X
rev.	description	date	name		

