

# VS-ST-KX-75-RG179/187


Order No.: 1655629



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=1655629>

Coaxial contact, for D-SUB combination inserts, solder cup, pin, straight, for cable RG 179/187, gold-plated

## Commercial data

GTIN (EAN)	
sales group	D502
Pack	10 pcs.
Customs tariff	85369010
Catalog page information	Page 325 (PC-2009)

## Product notes

WEEE/RoHS-compliant since:  
09/07/2006



<http://www.download.phoenixcontact.com>  
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

## Technical data

### Mechanical characteristics

Insertion/withdrawal cycles	≥ 500
Type of connection	Solder cup
Conductor cross-section	0.2 mm <sup>2</sup>

Connection cross-section AWG	24
External cable diameter	3.2 mm
Insertion force per signal contact	≤ 7.00 N
Extraction force per signal contact	≤ 7 N
Ambient temperature (operation)	-55 °C ... 135 °C

**Material data**

Contact material	Copper alloy
Contact surface material	Hard gold-plated over nickel

**Electrical characteristics**

Rated voltage (III/3)	250 V
Rated current	2 A
Insulation resistance	10 TΩ

**Accessories**

Item	Designation	Description
1676747	HC-M4-KOAX-EWZ	Contact removal tool for coaxial contacts

**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;