


## FLKM 50-PA-AB/1756



Order No.: 2296427

The illustration shows front adapter for Allen Bradley in design Control-Logix and Honeywell Plant-Scape



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2296427>

VARIOFACE front adapters, for ControlLogix, max. 1 x 32 channels can be connected, number of positions 50. The front adapters **cannot** be pushed into a hood!

Commercial data		Product notes
GTIN (EAN)		WEEE/RoHS-compliant since: 08/08/2006
sales group	I603	
Pack	1 pcs.	
Customs tariff	85369010	
Catalog page information	Page 144 (IF-2002)	
		<p><a href="http://www.download.phoenixcontact.com">http://www.download.phoenixcontact.com</a></p> <p>Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.</p>

Technical data	
<b>General</b>	
Nominal voltage $U_N$	< 50 V AC
	60 V DC
Channels which can be connected	32
Connection type, plug connector	Flat-ribbon cable plug connector in acc. with IEC 60603-13

Number of plug connectors	1
No. of positions, plug connector	50
Number of positions	50
Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C
Mounting position	Any
Standards/regulations	IEC 60664
	IEC 60664 A
	DIN VDE 0110
	DIN VDE 0160 (in parts)
Max. permissible current	1 A (per path)
	8 A (per connection, supply via separate power supply)
Pollution degree	2
Surge voltage category	II
Supported controller	ALLEN-BRADLEY ControlLogix
Supported I/O card	1756-IA16I
	1756-IB16D
	1756-IB16I
	1756-IH16I
	1756-OB32
	1756-IF8
	1756-IF16
	1756-HSC
	1756-M02AE
Supported controller	HONEYWELL PlantScape
Supported I/O card	TC-IDJ 161
	TC-IDX 161
	TC-IDK 161
	TC-ODD 321
	TC-IAH 161

#### Certificates / Approvals




Certification

CUL, GOST, UL

## Diagrams/Drawings

### Circuit diagram



**Address**

PHOENIX CONTACT Deutschland GmbH  
Flachsmarktstr. 8  
32825 Blomberg, Germany  
Phone +49 5235 3 12000  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.de>



© 2011 Phoenix Contact  
Technical modifications reserved;