



SIGN	DATE	DESCRIPTION	APPROVER
		<i>THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</i>	

SPECIFICATIONS

VOLTAGE & CURRENT: 300V, 30A
 WITHSTANDING VOLTAGE: AC 2000 V/Min
 INSULATION RESISTANCE: >1000 MΩ@DC 500 V
 TEMPERATURE RANGE: -40 °C ±105 °C
 SCREW TORQUE VALUE: 8.8 Lb-In.
 WIRE RANGE: 22 - 10 (str/sol) AWG

1) MOLDED PARTS: POLYIMIDE 66, UL 94 V-0 BLACK
 2) TERMINAL: BRASS, 0.8t, Tin PLATED
 3) TERMINAL SCREWS: STEEL, Ni PLATED, M3.5

● Safety Approval: **UL**
 RoHS Compliant

PART NUMBER:
OSTYK515XX330

No. of Poles ————
 02: 2 Poles
 03: 3 Poles
 04: 4 Poles
 :
 :
 30: 30 Poles



THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

TITLE		OSTYK-515 W/Flange Series, 9.5mm			
PART NO.		OSTYK515XX330		DWG NO.	OSTYK515XX330.DWG
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	UNIT: mm SCALE: NONE SHEET: 01/01 REV: B
Shi Jun 2006.11.07	Seamus 2006.11.06	Tony 2006.02.07	Tony 2006.02.07		
					Tolerance
					X. ±0.50
					X.X ±0.30
					X.XX ±0.10
					X* ±1*