



SIGN	DATE	DESCRIPTION	APPROVER
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

- Material**
- Terminal body(metal housing): Brass(CuZn),Ni plated
 - Terminal screw: Steel Zinc plating "-" slot type
 - Wire guard: PhBz ,Tin plated
 - Insulator (housing) Body: Thermoplastic (UL94V-0)
 - Insulator (housing) Cover: Thermoplastic (UL94V-0)

- Electrical cULus**
- Voltage rating: 300VAC
 - Current rating: 10A
 - Wire range:
 - Solid wire(AWG): 14-28
 - Stranded wire(AWG): 14-28
 - Torque: 1.7lb-in
 - Screw: M2
 - Wire strip length: 6-7mm
 - Withstanding Voltage: 1.6KV
 - Operating temperature: -40°C to +115°C
 - Safety Approval:

RoHS Compliant

PART NUMBER:

OSTE2XX1130

No. of Poles	COLOR
02 2 Poles	0: Black
03 3 Poles	3: Orange (Standard)
...	5: Green
24 24 Poles	6: Blue
	8: Grey

THESE DRAWINGS AND SPECIFICATIONS ARE THE PROPERTY OF ON-SHORE TECHNOLOGY, INC. AND SHALL NOT BE REPRODUCED, COPIED OR USED IN ANY MANNER WITHOUT THE PRIOR WRITTEN CONSENT OF ON-SHORE TECHNOLOGY, INC.

Poles	2p	3p	4p	5p	6p	7p	8p	9p	10p	11p	12p	13p	
Dim L	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0	45.5	
Dim B	3.50	7.00	10.5	14.0	17.5	21.0	24.5	28.0	31.5	35.0	38.5	42.0	
TOL	±0.15						±0.20						±0.25
Poles	14p	15p	16p	17p	18p	19p	20p	21p	22p	23p	24p		
Dim L	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5	84.0		
Dim B	45.5	49.0	52.5	56.0	59.5	63.0	66.5	70.0	73.5	77.0	80.5		
TOL	±0.25						±0.30						

TITLE		OSTE2 3.5 SERIES Without flange			
PART NO.	OSTE2XX1130	DWG NO.	OSTE2XX1130.DWG		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance
	Marvin 2008.05.16	Marvin 2008.02.26	Marvin 2008.02.26		X. ±0.50 X.X ±0.30 X.XX ±0.10 X* ±1*
				SHEET: 01/01	REV: A